

Item no.: 770-203  
 Product description: SOCKET WITHOUT RELIEF HOUSING 3 POLE PIN  
 SPACING 10 MM / 0.394 IN 100% PROTECTED AGAINST  
 MISMATING



Produkt kann von Bild abweichen / product may differ

Packing unit 100 pieces

RoHS compliant

|                                  |                         |
|----------------------------------|-------------------------|
| Product group                    | 20 (WINSTA)             |
| pole count                       | 3                       |
| Cross section [mm <sup>2</sup> ] | 0.5 - 4 mm <sup>2</sup> |
| Cross section [AWG]              | 20 - 12 AWG             |
| Connection method                | CAGE CLAMP®S Connection |
| Measured voltage EN              | 250 V                   |
| Measured shock voltage           | 4 kV                    |
| Pollution degree                 | 3                       |
| Current intensity EN             | 25 A                    |
| Weight                           | 9.504 g                 |
| Color                            | black                   |
| No. of connection Points         | 6                       |
| No. of potentials                | 3                       |
| Height                           | 12.9 mm                 |
| Height                           | 0.508 in                |
| Width                            | 30 mm                   |
| Width                            | 1.181 in                |
| Depth                            | 37.5 mm                 |

|                   |          |
|-------------------|----------|
| Depth             | 1.476 in |
| Strip length from | 9 mm     |
| Strip length to   | 9 mm     |
| Strip length      | 0.35 in  |



| Item no. | Admission office | Approval no.       | Voltage [V] | Current [A] | Cross section [ mm <sup>2</sup> ] |
|----------|------------------|--------------------|-------------|-------------|-----------------------------------|
| 770-203  | ABS              | 06-HG154986/11-PDA | 400         | 25          | 0,5-4,0                           |
| 770-203  | CBCertificateVDE | DE1-29543          | 250/400     | 25          | 0,5-4                             |
| 770-203  | CCA              |                    | 400         | 25          | 0,5-4,0                           |
| 770-203  | cURus            | E45171             | 600         | 20          | 12                                |
| 770-203  | DNV              | E-9217             | 250         | 25          | 4                                 |
| 770-203  | GL               | 42875-02HH         | 250         | 25          | 4                                 |
| 770-203  | KEMA             |                    | 250         | 25          | 0,5-4,0                           |
| 770-203  | LR               | 02/20050(E3)       | 250         | 25          | 2,5                               |
| 770-203  | PRS              | TE/1719/880590/08  | 250         | 25          | 0,5-4,0                           |
| 770-203  | PSE              | JET0695-43009-1001 | 600         | 20          | 12                                |
| 770-203  | VDE              | Ausweis.Nr.30726   | 250/400     | 16/25       | 0,5-4,0                           |

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected