

UNI-T® UT33 SERIES

Palm Size Digital Multimeters

UT33A



EN:61010-1
EN:61326-1



SPECIFICATIONS

Specifications	Range	Best Accuracy
Model		UT33A
DC Voltage (V)	400mV/4V/40V/400V/500V	±(0.8%+1)
AC Voltage (V)	4V/40V/400V/500V	±(1.2%+3)
DC Current (A)	400µA/4000µA/40mA/400mA/4A/10A	±(1%+2)
AC Current (A)	400µA/4000µA/40mA/400mA/4A/10A	±(1.5%+5)
Resistance (Ω)	400Ω/4KΩ/40KΩ/400KΩ/4MΩ/40MΩ	±(1%+2)
Features		
Display Count		3999
Auto Range		✓
Diode		✓
Transistor		✓
Continuity Buzzer		✓
Low Battery Indication		✓
Input Impedance for DCV	Around 10MΩ	✓



■ UT33A

GENERAL CHARACTERISTICS

Power	1.5V Batteries (R03)×2
LCD Size	48mm × 16mm
Product Color	Red and Grey
Product Net Weight	179g (Including Holster)
Product Size	130mm × 73.5mm × 35mm
Standard Accessories	Batteries, Test Lead, Holster
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	60 PCs
Standard Carton Measurement	490mm × 356mm × 315mm (0.055 CBM Per Standard Carton)
Standard Carton Gross Weight	18Kg