

PTSM 0,5/ 5-HV-2,5-THR R32


Order No.: 1778586



<http://eshop.phoenixcontact.sk/phoenix/treeViewClick.do?UID=1778586>

Header, Nominal current: 6 A, Rated voltage (III/2): 160 V, Number of positions: 5, Pitch: 2.5 mm, Color: Black, Contact surface: Tin, Assembly: SMD/THT/THR

Commercial data

EAN	 4 046356 529754
Pack	330 pcs.
Customs tariff	85369010
Catalog page information	Page 57 (CC-2011)

Product notes

WEEE/RoHS-compliant since:
17.09.2009



Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation at <http://www.download.phoenixcontact.com>. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Dimensions / positions

Length	5 mm
Pitch	2.5 mm
Dimension a	10 mm
Number of positions	5
Pin dimensions	0,6 x 0,6 mm
Pin spacing	2.50 mm


Hole diameter	1.1 mm
Technical data	
Range of articles	PTSM 0,5/...-HV-THR
Insulating material group	IIIa
Rated surge voltage (III/3)	2.5 kV
Rated surge voltage (III/2)	2.5 kV
Rated surge voltage (II/2)	2.5 kV
Rated voltage (III/2)	160 V
Rated voltage (II/2)	160 V
Connection in acc. with standard	EN-VDE
Nominal current I_N	6 A
Nominal voltage U_N	50 V
Maximum load current	6 A
Insulating material	LCP
Inflammability class according to UL 94	V0
Color	Black
Nominal voltage, UL/CUL Use Group B	150 V
Nominal current, UL/CUL Use Group B	6 A

Certificates


Certification CUL, GOST, UL

Drawings

Drilling plan/solder pad geometry



Dimensioned drawing



Connection data incl. use groups





Address

PHOENIX CONTACT, s.r.o.
Pribinova 25
Bratislava, Slovakia
Phone +420 542 213 401
Fax +421 2 3210 1479
<http://www.phoenixcontact.sk>

© 2012 Phoenix Contact
Technical modifications reserved;