


Item no.: 256-740  
 Product description: Modular PCB terminal block 2 solder pins/pole 1-pole Pin spacing 5/5.08 mm / 0.2 in



Produkt kann von Bild abweichen / product may differ

Packing unit 600 6\*100 pieces

RoHS compliant

Product group	4 (Printed Circuit)
Weight	0.946 g
Color	red
No. of connection Points	1
No. of potentials	1
pole count	1
Height	18.2 mm
Height	0.72 in
Width	5 mm
Width	0.197 in
Depth	17.6 mm
Depth	0.693 in
Pin spacing from	5 mm
Pin spacing up to	5.08 mm
Pin spacing from	0.197 in
Pin spacing up to	0.2 in
Rating based on	IEC/EN 60664-1
Overtoltage category EN I	III
Pollution degree	2

Measured voltage EN	320 V
Measured shock voltage	4 kV
Current intensity EN	24 A



Overvoltage category EN II	II
Pollution degree	2
Measured voltage EN	630 V
Measured shock voltage	4 kV
Current intensity EN	24 A
Overvoltage category EN III	III
Degree of pollution	3
Rated voltage EN	250 V
Rated surge voltage	4 kV
Nominal current	24 A
Connection method	CAGE CLAMP®CONNECTION
Cross section [mm²]	0.08 - 2.5 mm²
Wiring method	solid
Cross section [mm²]	0.08 - 2.5 mm²
Wiring method	fine-stranded
Cross section [mm²]	0.25 - 1.5 mm²
Wiring method	fine-stranded (with ferrule and plastic collar)
Cross section [mm²]	0.25 - 1.5 mm²
Wiring method	fine-stranded (with ferrule, without plastic collar)
Cross section [AWG]	28 - 12 AWG
Strip length from	5 mm
Strip length to	6 mm



Strip length from [inch]	0.2 in
Strip length up to [inch]	0.24 in
Conductor entry angle to the PCB (degrees)	45 °
Solder pin length [mm]	4 mm
Solder pin width A [mm]	0.7 mm
Solder pin width B [mm]	0.7 mm
Diameter of drilled hole [mm]	1.1 mm
Tolerance of drilled hole diameter [mm]	0.1 mm
Material group	I
Insulating material	PA 6.6
Temperature stability	-60 °C to +105 °C
Flammability category, based on UL 94	0V
Clamping spring material	Nickel-chromium spring steel (CrNi)
Contact material	Electrolytic copper (Ecu)
Contact plating	tin-plated

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected