

## Data sheet

262-306

## 2-CONDUCTOR TERMINAL BLOCK LATERAL MARKING SIDE-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE



## Technical data

Package size 100 2\*50 pieces.

Cross section from [mm <sup>2</sup> ]	0.08 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	4 mm <sup>2</sup>
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Voltage UL	300/600 V
Voltage CSA	300/600 V
Current UL	20/5 A
Current CSA	20/5 A
Measured voltage EN	630 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	24 A
Weight	4.13 g
Color	orange
Wiring type	Side-entry
No. of connection Points	2
No. of potentials	1
Height	23 mm
Height	0.906 in
Width	7 mm
Width	0.276 in
Depth	33.5 mm
Depth	1.32 in

---

**Data sheet**

**262-306**

**2-CONDUCTOR TERMINAL BLOCK LATERAL MARKING  
SIDE-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE**

---

Strip length from	9 mm
Strip length to	10 mm
Strip length	0.37 in

## Data sheet

262-306

### 2-CONDUCTOR TERMINAL BLOCK LATERAL MARKING SIDE-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

---

Approval	Voltage	Current	Approval number	Notes
BBJ	630	32	B/12/696/03	
BV			07436/C0	
CCA	630	32	DK96-00357	
CSA	300/600	20/5	18677-45	
CSM	630	32	017956	
DEMKO		24	120039/03	
Dep.MaE	300	34	CS4590N	
DNV	630	32	E6998	
FTZU	600	20/5	08Q040/Ex91.0158	
GL	630	32	17295-00HH	
KEMA	660		94.7117.02	
KR	630	32	HMB05880-EL002	
LR	750	35	91/20242(E3)	
NEMKO	500		L94015	
PRS	630	32	TE/1219/880590/98	
RMR	630	32	99.00007.250	
RosTesT	630	32	B09523	
UL	300/600	20/5	E45172	
VDE	660		2098ÜG,Bl.1	

## Data sheet

262-306

### 2-CONDUCTOR TERMINAL BLOCK LATERAL MARKING SIDE-ENTRY CAGE CLAMP CONNECTION HORIZONTAL TYPE

#### Accessories

#### Item number

ALUMINIUM CARRIER RAIL 1000 MM / 3' 3 IN LONG	210-154
COMB TYPE JUMPER BAR INSULATED	262-402
END PLATE WITH FIXING FLANGE	262-361
END STOP FOR WSB QUICK MARKERS	209-122
Individual wire jumpers	individual jumper
MODULAR TEST PLUG ADAPTER MODULAR	249-137
MOUNTING CARRIER CAN BE USED AS END PLATE	209-137
MOUNTING FOOT FOR MOUNTING ON RELAY-MODULES	209-120
MOUNTING FOOT WITH SCREW FOR TERMINAL BLOCKS WITH ALIGNABLE FIXINGS	209-123
Open individual wire jumpers ends	individual jumper open end
OPERATING STICKER FOR SIDE-ENTRY PCB TERMINAL BLOCKS	210-188/001-000
OPERATING TOOL TO CONNECT JUMPERS	209-132
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-257
SCREWDRIVER Type 2, bar (3,5 x 0,5) mm	210-120
SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 2, bar (3,5 x 0,5) mm	210-620
TEST PLUG 2 MM / 0.079 IN WIDE	210-136
TEST PLUG 2.3 MM / 0.091 IN WIDE	210-137