
Item no.: 2091-1404/005-000
Product description: Male header with straight solder pins and fixing flanges 4-pole
Pin spacing 3.5 mm / 0.138 in

Produkt kann von Bild abweichen / product may differ

RoHS compliant

Color	light grey
pole count	4
Height	17.5 mm
Height	0.689 in
Width	28 mm
Width	0.63 in
Depth	12.4 mm
Depth	0.488 in
Pin spacing from	3.5 mm
Pin spacing from	0.138 in
Rating based on	IEC/EN 60664-1
Overvoltage category EN I	III
Pollution degree	2
Measured voltage EN	160 V
Measured shock voltage	2.5 kV
Current intensity EN	10 A
Overvoltage category EN II	II
Pollution degree	2
Measured voltage EN	320 V
Measured shock voltage	2.5 kV
Current intensity EN	10 A
Overvoltage category EN III	III



Degree of pollution	3
Rated voltage EN	160 V
Rated surge voltage	2.5 kV
Nominal current	10 A
Solder pin length [mm]	3.6 mm
Solder pin width, diam. [mm]	1 mm
Diameter of drilled hole [mm]	1.2 mm
Tolerance of drilled hole diameter [mm]	0.1 mm
Material group	I
Temperature stability	-60 °C to +85 °C
Flammability category, based on UL 94	0V
Contact material	Electrolytic copper (Ecu)
Contact plating	tin-plated
Customs Tariff No.	85366990

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected