



Series	Material	Colour	Temp. Range	Min.Fluid S.G.
RSF41	Acetal Copolymer Hoechst Hostaform C9021	Red	-10 +60°C	0.875

UL File No.:- E103299 Applies to Reedswitch Only

ELECTRICAL SPECIFICATION – RESISTIVE LOADS						
	Contact Form	VA Rating	Breakdown Voltage	Switching Voltage		Switching Current Max.
				AC	DC	
Y	A25	25	800V dc	-	30	0.5
				-	120	0.15
				30	-	0.6
				120	-	0.15
				240	-	0.1

Leadout Wires 16/0.2 PVC Insulated 2.0 Metres Lg. Nominal

CRYDOM
LIMITED
7 COBHAM RD
FERNDOWN INDUSTRIAL EST.
WIMBORNE
DORSET
BH21 7PE
ENGLAND

CRYDOM LIMITED OWNS THE COPYRIGHT OF THIS DRAWING WHICH IS SUPPLIED IN CONFIDENCE AND MUST NOT BE USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SUPPLIED AND MUST NOT BE REPRODUCED WITHOUT PERMISSION IN WRITING FROM THE OWNERS
© CRYDOM LIMITED

Sheet No.	01	02	03	04	05	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27
Issue	01																										
Date	03/03/97																										
ECO	ECO 5787																										
Issue	01																										
Limits Not Shown	Date	Drawn	Prod.Eng.	Q.A. Eng.	Team Le.	CAD Ref																					
	03/03/97	T. TITLEY				V:\CAD\CADD6\OD\RSF41034																					
	Title	OUTLINE RSF41Y200ED034 FLOATSWITCH														Pt.No.	Drg No. OD403023										