

Single-deck terminal block - Modular version - Pitch 3,5mm - 2 / 3 poles

GENERAL INFORMATION

pitch:	3,5 mm
housing height:	8,40 mm
housing depth:	6.8 mm
dimensional class:	slow
wire section:	1.0 mm ² / 16 AWG
clamp opening size:	1.8 × 1.8 mm
wire stripping:	max 6 mm
operating temperature:	-40°C ÷ +105°C

ELECTRICAL CHARACTERISTICS

current:	10A
voltage:	130V
test voltage:	1.25 kVrms/60s

MECHANICAL CHARACTERISTICS

screw:	M2
max. torque:	0.2 Nm / 1.8 in.lbs


APPROVALS DATA



current:	-	-	UL 1059
voltage:	-	-	6A factory / 6A field
wire section:	-	-	300V
torque:	-	-	16÷24AWG
FILE:	-	-	1.8Lb-in
			E178356

MATERIALS

AVAILABLE COLOURS

housing: PA - UL 94 V0  (STD)
 screw: Galvanized steel
 clamp/spring: Tin-plated copper alloy other colours: upon request
 terminal: Tin-plated copper alloy

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
2	MLK132-3,5-V	N/A	N/A	N/A
3	MLK133-3,5-V	N/A	N/A	N/A
..	MLK13..-3,5-V	N/A	N/A	N/A