



VOLTCRAFT®

VOLTCRAFT® - TOP PERFORMANCE IN EVERY WAY

“For more than 25 years, our product range has been dynamically adapting to the constant changes in the industry. We commit to offering first-class quality to our customers while delivering an excellent cost-performance ratio. This philosophy remains the cornerstone of Voltcraft’s success.”

VC175 DIGITAL MULTIMETER

N° 124457

CE

VERSION 08/14

Robust digital multimeter featuring professional-class specifications and automatic range selection. The VC175 series is designed to cover all DIY measurement tasks. Professional jobs up to 600 V can be carried out, too.

HIGHLIGHTS

CAT III 600 V //

4000 counts //

Auto range //

Capacitance measurement //

Duty cycle //

Diode test //

Acoustic Continuity Tester //

Contactless AC voltage tester //

Auto power-off //

Rugged enclosure with soft rubber cover //



TECHNICAL DATA

Operating voltage	9 V block battery
Display	3999 count
Measuring frequency	approx. 2-3 measuring operations/second
Measuring lead length	approx. .75 cm
Measuring impedance	>10M Ω (V range)
Operation temperature	0 to +40 °C
Operation humidity	≤75 % (for 0 to +30 °C), ≤50 % (for +30 to +40 °C)
Operating altitude	max. 2000 m
Storage temperature	-10 to +50 °C
Dimensions (W x H x D)	75 x 150 x 38 mm
Weight	approx. 200 g

DC voltage

Range	Accuracy	Resolution
4000 V	±(0.8 % reading +8 digits)	1 V
40 mV		10 mV
400 V		100 V
600 V		1 V
Overload protection: 600 V Input impedance: approx. 4.5 M Ω Frequency response: 45 - 400 Hz Display: Sine wave valid value (average value response)		

AC voltage

Range	Accuracy	Resolution
400 mV	±(2.0 % reading +10 digits)	0.1 mV
4 mV	±(1.6 % reading +4 digits)	1 mV
40 V		0.01 V
400 V		0.1 V
600 V		1 V
Overload protection: 600 V Input impedance: approx. 4.5 M Ω Frequency response: 45 - 400 Hz Display: Sine wave valid value (average value response)		

DC current

Range	Accuracy	Resolution
400 μ A	±(1.3 % reading +3 digits)	0.1 μ A
4000 μ A		1 μ A
40 mA	±(1.6 % reading +2 digits)	10 μ A
400 mA		0.1 mA
4000 A	±(2.0 % reading +10 digits)	1 mA
10 A		10. mA
Overload protection: mA μ A range: F1 fuse 6 x 32 mm F 0.5 A H 600 V (CE) Item no.: 702632 10A range: F2 fuse 6 x 25 mm F 10 A H 600 V (CE) Item no.: 700161 Measuring operations of >5 A may only be performed for at most 10 seconds with a subsequent measuring pause of 15 minutes.		

AC current

Range	Accuracy	Resolution
400 μ A	$\pm(1.6\% \text{ reading} + 5 \text{ digits})$	0.1 μ A
4000 μ A		1 μ A
40 mA	$\pm(2.0\% \text{ reading} + 8 \text{ digits})$	10 μ A
400 mA		0.1 mA
4000 A	$\pm(2.6\% \text{ reading} + 4 \text{ digits})$	1 mA
10 A		10. mA
Overload protection: mA μ A range: F1 fuse 6 x 32 mm F 0.5 A H 600 V (CE) Item no.: 702632 10A range: F2 fuse 6 x 25 mm F 10 A H 600 V (CE) Item no.: 700161 Measuring operations of >5 A may only be performed for at most 10 seconds with a subsequent measuring pause of 15 minutes Frequency response: 45 – 400 Hz Display: Sine wave valid value (average value response)		

Resistance

Range	Accuracy	Resolution
400 Ω	$\pm(1.6\% \text{ reading} + 3 \text{ digits})$	0.1 Ω
4000 Ω		1 Ω
40 k Ω	$\pm(1.3\% \text{ reading} + 3 \text{ digits})$	10 Ω
400 k Ω		100 Ω
4 M Ω	$\pm(1.5\% \text{ reading} + 10 \text{ digits})$	1 k Ω
40 M Ω	$\pm(2.0\% \text{ reading} + 8 \text{ digits})$	10 k Ω
Overload protection: 600 V		

Diode / continuity test

Acoustic continuity tester: $\leq 10 \Omega$ permanent sound
Acoustic continuity tester resolution: 0.1 Ω
Diode test voltage: 1.5 V
Overload protection: 600 V

Non-contact voltage test

Target voltage: 230 V/AC

Capacitance

Range	Accuracy	Resolution
40 nF	Under REL status: $\pm(4\% \text{ reading} + 10 \text{ digits})$	10 pF
400 nF	Under REL status:	100 pF
4 μ F	$\pm(4\% \text{ reading} + 3 \text{ digits})$	1 nF
40 μ F	$\pm(4\% \text{ reading} + 3 \text{ digits})$	100 Ω
100 μ F	$\pm(5\% \text{ reading} + 10 \text{ digits})$	100 nF
Overload protection: 600 V		

Frequency / Duty Ratio

Range	Accuracy	Resolution
10 Hz - 10 MHz	$\pm(1.6 \% \text{ reading} + 3 \text{ digits})$	0.001 Hz - 0.001 MHz
0.1 - 99.9 %	$\pm(0.7 \% \text{ reading} + 4 \text{ digits})$	0.1 %

Overload protection: 600 V
Input amplitude a: (DC level is zero)
 $300 \text{ mV} \leq a \leq 30 \text{ Vrms}$ (for 10 Hz - 1 MHz)
 $600 \text{ mV} \leq a \leq 30 \text{ Vrms}$ (for >1 MHz - 10 MHz)

PACKAGE CONTENT

Digital multimeter / Measuring leads // Operating instructions

This data sheet is published by Conrad Electronic SE, Klaus-Conrad-Str. 1, D-92240 Hirschau (www.conrad.com).

All rights including translation reserved. Reproduction by any method, e.g. photocopy, microfilming, or the capture in electronic data processing systems require the prior written approval by the editor. Reprinting, also in part, is prohibited. This data sheet represents the technical status at the time of printing.