

Item no.: 273-158
 Product description: PUSH-WIRE CONNECTOR FOR JUNCTION BOXES; 8-CONDUCTOR TERMINAL BLOCK; PUSH-WIRE CONNECTION



Packing unit 500 10*50 pieces

pole count	8
Cross section from [mm ²]	0,75 mm ²
Cross section to [mm ²]	1,5 mm ²
Cross section from [AWG]	18 AWG
Cross section to [AWG]	16 AWG
Connection method	PUSH-WIRE CONNECTION
Number of strands	8
Voltage CSA	600 V
Voltage UL	600 V
Current UL	10 A
Current CSA	10 A
Measured voltage EN	400 V
Measured shock voltage	4 kV
Pollution degree	2
Current intensity EN	18 A
Weight	4,47 g
Color	transparent
Wiring type	Side-entry
No. of connection Points	8
No. of potentials	1
Height	8,6 mm
Height	0,339 in
Width	26 mm
Width	1,024 in
Depth	18,5 mm
Depth	0,728 in
Strip length from	10 mm
Strip length to	13 mm
Strip length	0,45 in

	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
273-158	ASTA	Cert.No.167	400	17,5	0,5-1,5
273-158	BBJ	B/12/694/03	400	17,5	1,5
273-158	BV	11914/AO	400	17,5	1,5
273-158	CCA	DK2017	400	17,5	1,5
273-158	CSA	154112-1059435	600	10	20-16"s"
273-158	CSM	017956	400	17,5	1,5
273-158	DEMKO	99-00683	400	17,5	1,5
273-158	DNV	E6998	400	17,5	1,5
273-158	FIMKO	FI13213	400	17,5	1,5
273-158	GL	17294-00HH	400	17,5	1,5

273-158	KEMA	97.1394.01	400	18	0,5-1,5
273-158	NEMKO	99101318	400	17,5	1,5
273-158	ÖVE	1193-033-00	400	17,5	1,5
273-158	RosTesT	B09523	400	17,5	1,5
273-158	SEMKO	9921002/01-03	400	17,5	1,5
273-158	SEV	99,770286,01	400	17,5	1,5
273-158	UL	E69654	600	10	20-16"s"
273-158	VDE	123900	400	17,5	1,5

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected