

Data sheet

231-639

MALE CONNECTOR 9 POLE CAGE CLAMP CONNECTION



Technical data

Package size 50 pieces.

Pin spacing from	5.08 mm
Pin spacing from	0.2 in
pole count	9
Cross section from [mm ²]	0.08 mm ²
Cross section to [mm ²]	2.5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Voltage UL	300 V
Voltage CSA	300 V
Current UL	15 A
Current CSA	15 A
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	12 A
Weight	14.02 g
Color	orange
No. of connection Points	9
No. of potentials	9
Height	14.3 mm
Height	0.563 in
Width	48.92 mm
Width	1.926 in

Data sheet**231-639****MALE CONNECTOR 9 POLE
CAGE CLAMP CONNECTION**

Depth	27.5 mm
Depth	1.083 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in
xxx-xxx/034-000	Strain relief plate 30 mm

Data sheet

231-639

MALE CONNECTOR 9 POLE CAGE CLAMP CONNECTION

Approval	Voltage	Current	Approval number	Notes
BBJ	250	16	B/12/699/03	
BV	400	16	11915/A0	
CCA	400	16	DK2127	
CSA	300	15	154112-1465035	
CSA	300	15	18677-30	
CSM	500/250	16	017956	
DEMKO	250		88126	
GL	400	16	17296-00HH	
KEMA	250	12	98.2486.01	
KR	250/400	12/16	HMB05880-EL003	
LR	400	16	96/20035	
NEMKO	250		P94101840	
RMR	400	16	99.00007.250	
RosTesT	400	16	B09523	
UL	600	15	E45171	
UL	300	15	E45172	
VDE	250	12	5675ÜGBI.2	

Data sheet

231-639

**MALE CONNECTOR 9 POLE
CAGE CLAMP CONNECTION**


Accessories**Item number**

CODING KEY FOR SNAP IN	231-129
COMB TYPE JUMPER BAR FOR PIN SPACING 5MM / 0.197 IN AND 5.08 MM / 0.2 IN	231-902
ISULATION STOP 0.08 - 0.2 MM ² / 0.2 MM ² S	231-670
ISULATION STOP 0.25 - 0.5 MM ²	231-671
ISULATION STOP 0.75 - 1 MM ²	231-672
LOCKOUT CAPS FOE COVERING UNUSED CLAMPING UNITS	231-669
OPERATING STICKER FOR MULTI CONNECTION SYSTEM	210-199
OPERATING TOOL FOR FEMALE AND MALE CONNECTORS WITH CAGE CLAMP	210-250
OPERATING TOOL TO CONNECT JUMPERS	209-132
PUSH BUTTON FOR FEMALE CONNECTORS AND MALE CONNECTORS	231-131
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-257
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-258
SCREWDRIVER Type 2, bar (3,5 x 0,5) mm	210-120
SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 2, bar (3,5 x 0,5) mm	210-620
SNAP-ON TYPE RELIEF HOUSING CONSISTING OF: STRAIN RELIEF SUPPORT/ HOUSING	232-639
SPACER FOR FORMATION OF GROUPS	231-500

Data sheet

231-639

MALE CONNECTOR 9 POLE
CAGE CLAMP CONNECTION



Data sheet

231-639

**MALE CONNECTOR 9 POLE
CAGE CLAMP CONNECTION**

A = (No.of poles x pin spacing) + 3,2 mm

B = A - 1,7 mm

C = A - 1,2 mm