

# UNI-T® UT15 SERIES

## Waterproof Type Voltage Testers

UT15A ■ UT15B ■ UT15C



■ UT15A



UT15B ■



■ UT15C

### SPECIFICATIONS



Specifications	Range	Best Accuracy		
		UT15A	UT15B	UT15C
Model	12V 24V 50V	0~12V 19V±2V 48V±6V	0~12V 19V±2V 48V±6V	0~12V 19V±2V 48V±6V
LED AC/DC Voltage Indication (V)	120V 230V 400V 690V	110V±20V 200V±20V 340V±30V 520V±30V	110V±20V 200V±20V 340V±30V 520V±30V	110V±20V 200V±20V 340V±30V 520V±30V
Phase Rotation Test	Operating Voltage: 0V~690V Frequency: 50Hz~60Hz	✓	✓	✓
Single Lead(L2)Voltage Detection	Operating Voltage: 0V~690V Frequency: 50Hz~400Hz	✓	✓	✓
Continuity Test	Resistance: 0~100KΩ Beeper and LED Light Indicator		✓	✓
Polarity Detection	Positive & Negative	✓	✓	✓
<b>Features</b>				
Water-Proof (IP65)		✓	✓	✓
Auto Range		✓	✓	✓
Work Light		✓	✓	✓
Low Battery Indication	Short circuit two leads,LED and beeper off when the battery is low	✓	✓	✓
LCD AC/DC Voltage Display	24V~690V			±(3%+5)

### GENERAL CHARACTERISTICS

Power	1.5V Batteries (R03) ×2
LCD Size	UT15C-23mm × 12mm
Product Color	Red and Grey
Product Net Weight	210g
Product Size	275mm × 51mm × 30mm
Standard Accessories	Batteries
Standard Individual Packing	Blister, English Manual
Standard Quantity Per Carton	30PCs
Standard Carton Measurement	440mm × 295mm × 455mm (0.079 CBM Per Standard Carton)
Standard Carton Gross Weight	17Kg