



| | | | |
|---|--|--|--------------------------|
| Model: LP383450 | | Overcharge Detection Voltage(V) 过充保护电压(V) | 4.28±0.05 |
| Min.Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量) | | Overdischarge Detection Voltage(V) 过放电保护电压(V) | 3.0±0.1 |
| Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量) | | Limited to Max loading current 仅用于最大的负载电流 peak value (A) 峰值 1 (A) | constant (A) 持续 1 (A) |
| Nominal Voltage 标称电压 (V) | | Customer required Max loading current 客户要求最大的负载电流 peak value (A) 峰值 2 (A) | constant (A) 持续 (A) |
| Internal impedance 内阻 (≅) (mΩ, AC 1KHz) | | Battery protection Related Value: (相关的电池保护值) | |
| Charge Temp. 充电温度 (°C) | | If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如实际应用的负载电流大于EEMB提供值, 请提出来, 实际的应用情况对PCM的设计至关重要) | |
| Discharge Temp. 放电温度 (°C) | | Remark(备注): | |
| Humidity(湿度) | | 1. No scratch, discoloration, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象). | |
| Ambient Conditions (环境温度) | | 2. Rohs compliant(严格按照ROHS要求生产). | |

| | | | | | |
|----------|--|------------|------------|-------------|---------|
| | | Drawn: | zhuhaoran | Revise No.: | E4-2009 |
| | | Checked 1: | Shannon | Projection: | |
| Title | | Checked 2: | | Page: | 1/1 |
| File NO. | | Approved: | | Scale: | 1:1 |
| A09151 | | Draw Date: | 2014/02/06 | Unit: | mm |