


Item no.: 243-724
 Product description: FEMALE CONNECTOR STRIP WITH TEST SLOT FOR SOLID WIRES PIN SPACING 5.75 MM / 0.226 IN CAN BE ASSEMBLED TO FEMALE STRIPS USING DOVETAIL JOINTS



Produkt kann von Bild abweichen / product may differ

Packing unit 400 pieces

RoHS compliant

Product group	7 (Push Wire Conn.)
Pin spacing from	5.75 mm
Pin spacing from	0.226 in
Cross section to [AWG]	18 AWG
Cross section to [AWG]	20 AWG
Cross section to [AWG]	22 AWG
Cross section to [AWG]	24 AWG
Diameter to	0.5 mm
Diameter to	0.6 mm
Diameter to	0.8 mm
Diameter to	1 mm
Measured voltage EN	100 V
Measured shock voltage	1.5 kV
Pollution degree	2
Current intensity EN	6 A
Weight	0.747 g
Color	light green
Wiring type	Side-entry

No. of connection Points	4
No. of potentials	1
Height	10 mm
Height	0.394 in



Width	5.75 mm
Width	0.226 in
Depth	10.5 mm
Depth	0.413 in
Strip length from	5 mm
Strip length to	6 mm
Strip length	0.22 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
243-724	ABS	04-HG476172/1-PDA	100	6	0,5-0,75
243-724	ABS	10-HN17750340X	100	6	4x0,5-1,0
243-724	CSA	18677-31	150	7	22-20
243-724	KEMA	2123448.01	100	6	0,5-1,0 sol
243-724	RMR	11130002	100	6	0,5-0,75

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected