
Item no.: 2002-3217
Product description: Triple-deck terminal block Ground conductor/through/through terminal block PE/N/L without marker carrier gray housing suitable for Ex e II applications



Produkt kann von Bild abweichen / product may differ

Packing unit 50 pieces

RoHS compliant

Current intensity EN	28 A
Product group	22 (TOPJOB S RAIL-MOUNTED TERMINAL BLOCKS)
Number of levels	3
Cross section [mm ²]	0.25 - 2.5 mm ²
Cross section [AWG]	22 - 12 AWG
Connection method	CAGE CLAMP®S Connection
Cross section [mm ²]	0.25 - 4 mm ²
Cross section [AWG]	22 - 12 AWG
Wiring method	s + f-st
Connection method	CAGE CLAMP®S Connection
Measured voltage EN	500 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	24 A
Weight	19.704 g
Color	grey
Wiring type	Front-entry

No. of connection Points	6
No. of potentials	3
Height	69.5 mm
Height	2.736 in
Width	5.2 mm



Width	0.205 in
Depth	93.5 mm
Depth	3.681 in
Strip length from	10 mm
Strip length to	12 mm
Strip length	0.43 in
Customs Tariff No.	85369010
Country of Origin	Deutschland
Mounting	TS 35



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
2002-3217	AEX	E185892			22-12
2002-3217	CCA	NL6387			0,2-2,5/4
2002-3217	CSA	154112-1536069			22-12
2002-3217	GL	6187-05HH			4,0
2002-3217	KEMA	NL2116586.02			0,2-4
2002-3217	LR	91/20112(E6)			4,0
2002-3217	PTB	IECExPTB03.0004U			0,2-4
2002-3217	PTB	PTB03Atex1162U			0,2-4
2002-3217	RosTest	8189158			0,2-4
2002-3217	UR	E45172			22-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected