

Breath Odor Checker



Breathe-N-Go

Pulling the ring starts operation and the operation automatically ends after measurement.

- Odor degree is classified with 6 levels
The level is displayed with numerical values from 1 to 6.
- Small size and light weight
Good portability with small size (74 (H) × 35 (W) × 19 (D) mm).

FIS
A Nissha Company

Breath odor checker (Breathe-N-Go) can easily check your breath odor.
Measurement is quite simple, just exhale into the checker.
The result is quickly displayed on the checker with 6 level judgment.

Item	Contents
Model No.	FBC-101
Sensor	Semiconductor gas sensor
Target gas	Various gases in breath
Sampling method	Direct exhaling into the checker
Start / end	Automatic start by pulling the ring, and auto-power off
Warming up time	5 seconds after power-on
Exhaling time	About 3 seconds
Displayed	Measurement result, battery life
Life time	Total of 500 time measurements
Result display	6 levels with LCD
Power supply	One AAA alkaline dry cell (1.5V DC) * The battery is not attached with the product.
Power consumption	300mW (max) during operation
Size	74 (H) × 35 (W) × 19 (D) mm
Material	Enclosure: PC resin, Display lens: Acryl
Weight	About 45 g including battery
Operating temperature and humidity	5 to 35°C, below 80%RH (No dew condensation)
Storage temperature and humidity	-10 to 50°C, 20 to 80%RH (No dew condensation)

HOW TO OPERATE

1. Place the battery in right position.
2. Pull the ring handle.
3. Wait until count-down is finished (about 5 seconds).
4. Continuously exhale into the exhaling inlet of the checker, about 3 seconds.
5. The result is automatically displayed and disappears in 5 seconds.
6. Shake the checker to delete gas around the sensor.
7. If you continue operation, push the ring and repeat the above procedures 1. to 6.

Note

- Rinse your mouth thoroughly with water immediately after brushing your teeth, eating food, and drinking, or wait more than 10 minutes before using the checker.
- The checker may not respond to certain gases in breath.
- Use or store in a place free from scents or odors, which may affect the reading.
- If battery mark blinks, replace the battery.
- If the product reaches its life time (600 usages), you cannot use the product.

The specifications and external design may be changed without notice.

CONTACT

FIS Inc. Headquarter
 3-36-3 Kitazono, Itami, Hyogo 664-0891
 Tel : +81-72-780-1800
 Fax : +81-72-785-0073
 URL : <http://www.fisinc.co.jp>