

## Data sheet

243-308

## MICRO PUSH-WIRE CONNECTOR FOR JUNCTION BOXES 8-CONDUCTOR TERMINAL BLOCK



## Technical data

Package size 500 10\*50 pieces.

pole count	8
Voltage UL	125 V
Voltage CSA	150 V
Current UL	7 A
Cross section from [AWG]	22 AWG
Cross section to [AWG]	87 AWG
Diameter from	0.6 mm
Diameter to	0.8 mm
Measured voltage EN	100 V
Measured shock voltage	1.5 kV
Pollution degree	2
Current intensity EN	6 A
Weight	1.44 g
Color	light grey
Wiring type	Side-entry
No. of connection Points	8
No. of potentials	1
Height	6.8 mm
Height	0.268 in
Width	18.4 mm
Width	0.725 in
Depth	10 mm
Depth	0.394 in

---

**Data sheet**

**243-308**

**MICRO PUSH-WIRE CONNECTOR FOR JUNCTION BOXES 8-CONDUCTOR  
TERMINAL BLOCK**

---

Strip length from	5 mm
Strip length to	6 mm
Strip length	0.22 in

---

Data sheet

243-308

**MICRO PUSH-WIRE CONNECTOR FOR JUNCTION BOXES 8-CONDUCTOR  
TERMINAL BLOCK**

---

Approval	Voltage	Current	Approval number	Notes
CCA	100	6	DK97-01026	
CSA	150		18677-31	
CSM	100	6	017956	
DEMKO	100	6	105047	
KEMA	100	6	92.6146.01	
RMR	100	6	99.00007.250	
RosTesT	100	6	B09523	
SEMKO	100	6	9144043	
UL	125	7	E45172	
VDE	100	6	2574-1440-4031	

---

**Data sheet**

243-308

**MICRO PUSH-WIRE CONNECTOR FOR JUNCTION BOXES 8-CONDUCTOR  
TERMINAL BLOCK**

---

**Accessories**

**Item number**

FIXING CARRIER FOR 4 PUSH-WIRE CONNECTORS

243-112

FIXING CARRIER FOR 6 PUSH-WIRE CONNECTORS

243-113