

RFID proximity card reader

Model: ACM118

Main Feature:

1. Frequency: 125Khz or 13.56Mhz
2. Dimension: 75*116*11mm
3. IP65 Waterproof

Feature:

Features:

- 1.Frequency: 125Khz or 13.56Mhz
- 2.Standard wiegand26 bit output, Optional WG34
- 3.Easy to install on Metal Door Frame or Mullion;
- 4.External LED Control;
- 5.External Buzzer Control;
- 6.Indoor / Outdoor Operation;
- 7.Solid Epoxy Potted;
- 8.Waterproof IP65;
9. Reverse Polarity Protection.

Specifications:

Model	ACM118-EM	ACM118-MF
Read Range	Up to 10CM	Up to 5CM
Reading Time (Card)	≤300ms	
Power / Current	DC 6-14V / Max.70mA	
Input Port	2ea (External LED Control, External Buzzer Control)	
Output Format	26bit Wiegand (default)	
LED Indicator	2 Color LED Indicators(Red and Green)	
Beeper	Yes	
Operating Temperature	-20° to +65°C	
Operating Humidity	10% to 90% relative humidity non-condensing	
Color	Black	
Material	ABS+PC with texture	
Dimension(W x H x T)mm	75*116*11mm	
Index of Protection	IP65	