



● UT603

UT600 series digital inductance capacitance meters are used to test resistors, capacitors and inductors. They can also be used to measure transistor parameters. These meters can be used to check electronic components in electronic labs, production lines, maintenance facilities and schools.

SPECIFICATIONS

	Range	UT601	UT602	UT603
Resistance (Ω)	20Ω/200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/200MΩ/2000MΩ	±(0.8%+1)		
	20Ω/200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ/2000MΩ		±(0.8%+1)	
	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ			±(0.8%+1)
Capacitance (F)	200pF/2nF/20nF/200nF/2uF/20uF/200uF/2mF/20mF	±(0.5%+10)		
	2nF/20nF/200nF/2uF/20uF/200uF/600uF			±(1%+5)
Inductance (H)	2mH/20mH/200mH/2H/20H/200H		±(2%+8)	
	2mH/20mH/200mH/2H/20H			±(2%+8)

Features

Display count		2000	2000	2000
Manual range		√	√	√
Diode		√	√	√
Transistor		√	√	√
Continuity buzzer		√	√	√
Low battery indication		√	√	√
Data hold			√	

GENERAL CHARACTERISTICS

Power	9V battery (6F22)
Display	61mm x 32 mm
Product color	Red and grey
Product net weight	UT601/UT602: 310g, UT603: 312g
Product size	172mm x 83mm x 38mm
Standard accessories	Battery, test leads with alligator clips, holster
Standard individual packing	Gift box, English manual
Standard quantity per carton	20pcs
Standard carton measurement	450mm x 330mm x 340mm (0.099CBM per standard carton)
Standard carton gross weight	9.6kg