

Data sheet

736-312

TRIPLE DECK PCB TERMINAL STRIP 2 SOLDER PINS IN LINE
PIN SPACING 5.08 MM / 0.2 IN FRONT-ENTRY CAGE CLAMP CONNECTION



Technical data

Package size 28 pieces.

Pin spacing from	5.08 mm
Pin spacing from	0.2 in
pole count	12
Cross section from [mm ²]	0.08 mm ²
Cross section to [mm ²]	2.5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Voltage UL	300 V
Voltage CSA	300/600 V
Current UL	10 A
Current CSA	10 A
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	12 A
Measured voltage EN	500 V
Measured shock voltage	4 kV
Pollution degree	2
Current intensity EN	12 A
Weight	27.44 g
Color	orange
Wiring type	Angled Type
No. of connection Points	24

Data sheet

736-312

**TRIPLE DECK PCB TERMINAL STRIP 2 SOLDER PINS IN LINE
PIN SPACING 5.08 MM / 0.2 IN FRONT-ENTRY CAGE CLAMP CONNECTION**

No. of potentials	24
Height	26.5 mm
Height	1.04 in
Width	61.96 mm
Width	2.439 in
Depth	21 mm
Depth	0.827 in
Strip length from	5 mm
Strip length to	6 mm
Strip length	0.22 in

Data sheet

736-312

**TRIPLE DECK PCB TERMINAL STRIP 2 SOLDER PINS IN LINE
PIN SPACING 5.08 MM / 0.2 IN FRONT-ENTRY CAGE CLAMP CONNECTION**

Approval	Voltage	Current	Approval number	Notes
BBJ	250	12	B/12/697/03	
BV	250	12	11915/A0	
CCA	250	12	DK2079	
CSA	300/600	10	18677-46	
CSM	250	12	017956	
DEMKO	250	12	99-04356	
DNV	250	12	E6998	
GL	250	12	17296-00HH	
RMR	250	12	99.00007.250	
RosTesT	250	12	B09523	
UL	300	10	E45172	

Data sheet

736-312

TRIPLE DECK PCB TERMINAL STRIP 2 SOLDER PINS IN LINE PIN SPACING 5.08 MM / 0.2 IN FRONT-ENTRY CAGE CLAMP CONNECTION

Accessories

	Item number
Jumper GDS RM 5mm	Jumper PCB Spacing 5mm
Jumper GDS RM 7,5mm	Jumper PCB Spacing 7.5mm
OPERATING STICKER FOR PCB TERMINAL BLOCKS Profile PCB 236, 255, 256	210-406 Profile PCB 236, 255, 256
Profile PCB 257, 736, 737, 738	Profile PCB 257, 736, 737, 738
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-257
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-258
SCREWDRIVER Type 2, bar (3,5 x 0,5) mm	210-120
SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 2, bar (3,5 x 0,5) mm	210-620
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 5.08 MM	249-166
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 5.08 MM	249-167
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 5.08 MM	249-168
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 5.08 MM	249-169