Item no.:	294-5453
Product description:	TERMINAL BLOCK FOR FIELD CONNECTION With PE screwed contact WITH SNAP-IN MOUNTING FEET 1 / PE / N 3 POLE



Produkt kann von Bild abweichen / product may differ

Packing unit 500 pieces

RoHS compliant

Color	white
pole count	3
Height	21.53 mm
Height	0.848 in
Width	30 mm
Width	1.181 in
Depth	27.3 mm
Depth	1.075 in
Pollution degree	2
Measured voltage EN	500 V
Measured shock voltage	4 kV
Current intensity EN	24 A
T Identification	T 85
Pollution degree	2
Measured voltage EN	500 V
Measured shock voltage	4 kV
Current intensity EN	24 A
T Identification	T 85

Connection method	CAGE CLAMP®S Connection
Cross section [mm²]	0.5 - 2.5 mm²
Cross section [AWG]	18 - 12 AWG
Wiring method	solid, stranded or fine-stranded

Number of strands	2
Cross section [mm²]	0.5 - 1.5 mm²
Cross section [AWG]	18 - 14 AWG
Wiring method	with ferrule
Number of strands	2
Connection method	PUSH WIRE®
Cross section [mm²]	0.5 - 2.5 mm²
Cross section to [AWG]	18 - 14 AWG
Wiring method	Solid
Cross section [mm²]	0.5 - 1.5 mm²
Cross section to [AWG]	18 - 14 AWG
Wiring method	with ferrule
Cross section from [mm²]	0.5 mm²
Cross section to [mm²]	1.5 mm²
Cross section from [AWG]	18 AWG
Cross section to [AWG]	16 AWG
Wiring method	Solid
Cross section from [mm²]	0.5 mm²
Cross section to [mm²]	1 mm²
Cross section from [AWG]	18 AWG
Cross section to [AWG]	16 AWG
Wiring method	with ferrule

Cross section from [mm²]	0.5 mm²
Cross section to [mm²]	0.75 mm²
Cross section from [AWG]	18 AWG
Wiring method	solid
Strip length from	8 mm
Strip length to	9 mm
Material group	IIIa

© WAGO Kontakttechnik GmbH & Co. KG
Specifications are subject to changes and errors may be expected