


U.I. Lapp GmbH	PRODUCT INFORMATION	
	SKINDICHT® SVF	29.11.2013

High mechanical stability
 Lateral sealing lips fit automatically around various cable dimensions
 Optimum strain relief
 Large opening allows clamping of up to two flat cables



Robust

Application range

For inserting flat cables.
 Conveyor systems
 Pumps
 Lifts
 Control cabinet manufacturing

Design

PG connection thread

Note

For suitable flat cables, refer to ÖLFLEX® LIFT F for indoor applications or ÖLFLEX® CRANE F for outdoor applications
 Counter nut to be used: SKINDICHT® SM

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Caution:	The installation dimensions can be found in appendix T21
On request:	Available with long connection thread
Material:	Body: nickel-plated brass Special sealing insert: CR
Protection rating:	IP 54
Temperature range:	-20°C to +100°C




Product Management	Document: LAPP_PRO1083EN.pdf	1 / 3
--------------------	------------------------------	-------




SKINDICHT® SVF

29.11.2013

Part number	Article designation / size	Min./max. flat cable width	Min./max. cable thickness (mm)	SW1/SW2 mm	Overall length/ C (mm)	Thread length/ D (mm)
SKINDICHT® SVF						
52005480	PG 16	-- 16	-- 5	24 / 22	27,5	6.5
52005490	PG 21	9 - 21	3 - 8	30 / 28	30.0	7.0
52005500	PG 29	14 - 30	4 - 11,5	40 / 37	31,5	8.0
52005510	PG36	24 - 40	4 - 11,5	50 / 47	36.0	9.0
52005520	PG 42	29 - 45	5 - 12	57 / 54	40.0	10.0
52005530	PG 48	34 - 50	5 - 12	64 / 60	41,5	10.0

U.I. Lapp GmbH	PRODUCT INFORMATION	 LAPP GROUP
	SKINDICHT® SVF	29.11.2013



Product Management	Document: LAPP_PRO1083EN.pdf	3 / 3
--------------------	------------------------------	-------