


Item no.: 243-204
 Product description: MICRO PUSH WIRE® connector for junction boxes 4-conductor terminal block



Produkt kann von Bild abweichen / product may differ

Packing unit 1000 10*100 pieces

RoHS compliant

Cross section [mm ²]	0.6 - 0.8 mm ²
Number of strands	4
Product group	7 (Push Wire Conn.)
pole count	4
Cross section to [AWG]	20 AWG
Cross section [AWG]	22 - 0.6 mm
Diameter to	0.8 mm
Measured voltage EN	100 V
Measured shock voltage	1.5 kV
Pollution degree	2
Current intensity EN	6 A
Weight	0.77 g
Color	dark grey
Wiring type	Side-entry
No. of connection Points	4
No. of potentials	1
Height	6.8 mm
Height	0.268 in
Width	10 mm

Width	0.394 in
Depth	10 mm
Depth	0.394 in



Strip length from	5 mm
Strip length to	6 mm
Strip length	0.22 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
243-204	ABS	04-HG476172/1-PDA	100	6	0,5-0,75
243-204	ABS	10-HN17750340X	100	6	4x0,5-1,0
243-204	CSA	18677-31	150	7	22-20
243-204	KEMA	2123448.01	100	6	05-1,0 sol
243-204	LR	04/20013(E3)	100	6	0,5-0,75
243-204	RMR	11130002	100	6	0,5-0,75
243-204	UR	E45172	150	7	22-18

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected