



- DC fans with electronically commutated external rotor motor. Fully integrated commutation electronics.
- With electronic protection against reverse polarity, blocking and overloading; partially impedance protected.
- Fan of fibreglass reinforced plastic. PBTP housing, PA impeller.
- Air exhaust over struts. Rotational direction CCW looking at rotor.
- Electrical connection via leads AWG 24, TR 64. Stripped and tinned ends.
- Mass 100 g.

**Series 3400 N 92 x 92 x 25 mm VARIOFAN**

	Air flow		Nominal Voltage	Voltage Range	Noise	Sinter-Sleeve Bearings		Power Input	Nominal Speed	Temperature Range	Service Life L <sub>10</sub>		Curve	Type	Specials
	m <sup>3</sup> /h	CFM				V DC	V DC				dB(A)	bels			
30-50 °C	44	25.9	12	8...14	14	3.5	□	1.5	1400	-20...+70	75 000/37 500		1	3412 NGMV	65
	72	42.4			28	4.6	■	2.0	2300		2				
30-50 °C	50	29.5	12	8...12.6	16	3.7	□	1.6	1600	-20...+70	75 000/37 500		3	3412 NGV	65
	84	49.4			32	5.0	■	2.5	2700		4				

DC Axial Fans

