


Item no.: 859-708  
 Product description: OPTOCOUPLER TERMINAL BLOCK FOR AVERAGE SWITCH ABILITIES NEGATIVE SWITCHING



Produkt kann von Bild abweichen / product may differ

Packing unit 25 25\*1 pieces

RoHS compliant

Product group	6 (Electronics)
Nominal input voltage (Un) (DC)	DC 24 V
Input voltage range, low level	DC 0-5 V
Input voltage range, high level	DC 19-30 V
Input current range	5,7-10,2 mA
Input circuit	REVERSE VOLTAGE PROTECTION
Nominal output voltage (DC)	24 V
Output voltage range	DC 20 V ... 30 V
max. continuous current (mA)	500 mA
Output circuit	RECOVERY DIODE, OPERATION INDICATION LED (RED)
Reverse voltage transistor (DC)	80 V
Pull-in time (µs)	< 10 µs
Drop-out time (µs)	< 10 µs
Max. operating frequency	10 kHz
Max. frequency at RL = 470 Ohm (kHz)	25 kHz
Leakage current at rated voltage	< 10 µA
Collector / emitter voltage drop Uce sat (<)	< 1,2 V
Max. output (reverse current) without load	11 mA

Test voltage input / output	2.5 kV
Normal operating method	100 % ED
Ambient operating temperature	-25 °C ... +55 °C
Storage temperature	-40 °C ... +70 °C



Standards	IEC60664, VDE0110 CORRESPOND. PARTS; POLLUTION DEGREE 2; OVERVOLTAGE CATEGORY III; DIN EN 50178, VDE 0160
Cross section [mm <sup>2</sup> ]	0.08 - 2.5 mm <sup>2</sup>
Cross section [AWG]	28 - 14 AWG
Weight	19.861 g
Color	gray
Wiring type	Front-entry
No. of connection Points	5
No. of potentials	5
Height	56 mm
Height	2.205 in
Width	6 mm
Width	0.236 in
Depth	91 mm
Depth	3.58 in
Strip length from	5 mm
Strip length to	6 mm
Strip length	0.22 in
Mounting	TS 35



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [ mm <sup>2</sup> ]
859-708	UL	02 ATEX132280 U			
859-708	UL	DK-7575			
859-708	UL	E175199 Sec.4			
859-708	UL	E198726 Sec.3			

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected