

Wiha crimp tools.

Crimp tools.



Z 62 0001 06 Crimp tools for wire-end sleeves.

Head shape: Square crimp, linear pressing.
Design: Tool with only one crimp profile.
Automatic adjustment of cross-section area.

Lateral contact feed.
Low hand force required with optimal transmission.
Detachable force lock for ensuring complete crimping process; required crimp pressure is factory set.
Ergonomically formed soft handle with slip protection for especially comfortable handling.
Of high-tensile special steel.
Material: Parts subject to extreme loading are specially hardened and tempered.
Application: For processing of wire-end sleeves with and without isolating collar according to DIN 46228, EN 50027.
Especially suitable for processing twin sleeves.

Order-No.	mm	Ømm	AWG	↔	↔	↔
33845	196	0.08 - 10	28 - 8	300	1	1

Crimp tools.



Z 62 0002 06 Crimping tools for isolated cable eyes and contacts.

Head shape: Oval crimp, radial pressing.
Design: Conducting and isolating crimp are carried out in one work step.

Crimp profile: **Red profile:** 0.5 - 1.0 mm² / AWG 20 - 16
Blue profile: 1.5 - 2.5 mm² / AWG 16 - 14
Yellow profile: 4.0 - 6.0 mm² / AWG 12 - 10
Detachable force lock for ensuring complete crimping process; required crimp pressure is factory set. Ergonomically formed soft handle with slip protection for especially comfortable handling.

Material: Of high-tensile special steel.
Application: Parts subject to extreme loading are specially hardened and tempered.
For processing of red, blue and yellow isolated cable eyes, pin-end cable connectors, contact pins, contact pin sleeves, circular pins, circular pin sleeves, batch connectors and parallel connectors according to DIN 46234.
For standardised, solderless electrical connections.

Order-No.	mm	Ømm	AWG	↔	↔	↔
33841	220	0.5 - 6	20 - 10	510	1	1



Z 62 0001 05 Crimp tools for wire-end sleeves.

Head shape: Trapezoid crimp, radial lateral.
Design: Crimp profile:

Profile 1: 0.14 - 0.75 mm² / AWG 26 - 18
Profile 2: 1.0 - 1.5 mm² / AWG 18 - 16
Profile 3: 2.5 mm² / AWG 14
Profile 4: 4.0 mm² / AWG 12
Profile 5: 6.0 mm² / AWG 10
Profile 6: 10.0 mm² / AWG 8

Detachable force lock for ensuring complete crimping process; required crimp pressure is factory set. Ergonomically formed soft handle with slip protection for especially comfortable handling.

Material: Of high-tensile special steel.
Application: Parts subject to extreme loading are specially hardened and tempered.
For processing of wire-end sleeves with and without isolating collar according to DIN 46228, EN 50027.

Order-No.	mm	Ømm	AWG	↔	↔	↔
33844	220	0.14 - 10	26 - 8	510	1	1

Wiha crimp tools and stripping pliers.

Crimping tools and stripping pliers.



Z 62 0003 06 Crimping tools for non-isolated contact pins.

Head shape: B-crimp, radial pressing.
Design: Conducting and isolating crimp are carried out in one work step.

Crimp profile: Contact width 6.3 / 9.5 mm
Profile 1: 0.25 - 0.5 mm² / AWG 22 - 20 / F 6.3 + 9.5
Profile 2: 0.5 - 1.0 mm² / AWG 20 - 16 / F 6.3 + 9.5
Profile 3: 1.5 - 2.5 mm² / AWG 16 - 14 / F 6.3 + 9.5
Profile 4: 4.0 - 6.0 mm² / AWG 12 - 10 / F 6.3 + 9.5
Detachable force lock for ensuring complete crimping process; required crimp pressure is factory set. Ergonomically formed soft handle with slip protection for especially comfortable handling.

Material: Of high-tensile special steel.
Application: Parts subject to extreme loading are specially hardened and tempered.
For processing of non-isolated contact pins and contact pin sleeves according to DIN 46247 for standardised solderless electrical connections.

Order-No.	mm	Ømm	AWG	↔	↔	↔
33842	220	0.25 - 6	22 - 10	510	1	1

Stripping pliers and stripping cassette.



246755B Automatic stripping pliers.

Design: Self-adjusting straight cutting edge in exchangeable cassette and wire cutter for copper and Al conductors. Optimally positioned wire cutter enables effortless cutting of multi-wire conductors to 10 mm² / 8 AWG. Simply replaceable stripping cassette with adjustable stripping length to 18 mm and adjustable cutting depth for various insulation materials. Ergonomically sophisticated solution with soft plastic zone in main handle, secure gripping without play, optimised handle opening width, an angled head as well as a low weight for working without fatigue.
Housing of tough glass-fibre reinforced plastic.
Material: Soft plastic zone in upper handle section used for gripping.
Application: For precise stripping and cutting of single, multi and fine-wired cables for many tasks in the electronics industry.

Order-No.	mm	ii	Ømm	AWG	↔	↔
33847	190	7%	0.02 - 10	34 - 8	1:35	1



246755S Automatic stripping pliers.

Design: Automatic setting to various conductor diameters. Settable length stop from 5 - 12 mm, can be removed if required. Integrated, easily accessible wire cutter.
Light, ergonomically designed tool body with narrow head for optimal use in hard-to-reach areas.
Locking for safe, space-saving transport.
Material: Housing of glass-fibre reinforced polyamide.
Application: Stripping of all commonly used flexible and solid conductors from 0.2 - 6.0 mm² (24 - 10 AWG).
Wire cutter for cutting of Cu and Al conductors to max. 0.2 mm.

Order-No.	mm	ii	Ømm	AWG	↔	↔
36050	190	7%	0.2 - 6.0	24-10	1:10	1



246755S Stripping cassette for automatic stripping pliers.

Design: Blister packed.
Cassette with straight blade.

Order-No.	Ømm	AWG	↔	↔
33846	0.02 - 10	34 - 8	7	1