



Model: LP503759		Overcharge Detection Voltage(V)	4.28±0.05
Battery pack specification (电池组规格)	Min.Capacity 最低容量(mAh) (0.2C,25±3°C) *Single cell capacity (单体电芯容量)	Overdischarge Detection Voltage(V)	2.3±0.1
	Typical Capacity 典型容量(mAh) (0.2C,25±3°C) *Single cell capacity (单体电芯容量)	过放保护电压(V)	Limited to Max loading current 仅用于最大的负载电流 峰值 2 (A) 持续 1 (A)
Ambient Conditions (环境温度)	Nominal Voltage 标称电压(V)	客户要求的最大负载电流 峰值 2 (A) 持续 1 (A)	constant (A) 持续 (A)
	Internal impedance 内阻(≅) (mΩ,AC 1KHz)	客户要求的最大负载电流 峰值 2 (A) 持续 1 (A)	constant (A) 持续 (A)
	Charge Temp. 充电温度(°C)	If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如实际应用的负载电流大于EEMB提供值, 请提出来, 实际的应用情况对PCM的设计至关重要)	
Discharge Temp. 放电温度(°C)	Humidity(湿度)	Remark(备注):	
	Humidity(湿度)	1. No scratch, discoloration, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象). 2. Rohs compliant(严格按照ROHS要求生产).	

Title		LP503759-PCM-LD/	
File NO.		A09154	
Drawn:		zhuhaoran	Revise No.:
Checked 1:		Shannon	Projection:
Checked 2:			Page:
Approved:			Scale:
Draw Date:		2014/02/06	Unit:
			mm

