



P1



P2

PIN ASSIGNMENT		
P1		P2
1	RED	1
2	WHITE	2
3	GREEN	3
4+5	BLACK	4
SHELL	DRAIN + BRAID	SHELL



Material:

- Cable: USB2.0 UL2725 [28AWG(7/0.12TC+AL)*1P+ 28AWG(7/0.12TC)*2C]+AEB(48B TC)
 - Jacket: Black
 - OD: 3.5MM
- Connector: Micro USB 5P A/M Solder Type
 - Shell: Nickel
 - Pin: G/F
 - Insulator Color: White
- Outer Jacket: Black PVC-50P

Electrical:

- 100% short, open, miswire test
- Conduct resistance: 3Ω Max.
- Insulation resistance: 20MΩ Min.
- Hi-Pot test: 300V DC

⊕ = Assmann logo



ITEM NO.	AK67321-1-R
TITLE	USB2.0 Micro Connection Cable, 1 Meter USB A Micro Male <=> USB A Male

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
Toll Free: 1-877-277-6266 • eMail: info@assmann.us

THIS DRAWING IS UNPUBLISHED
©Copyright 2009 by Assmann Electronic Components
All International Rights Reserved