MG1xx-5,08-P



GENERAL INFORMATION

pitch:	5,08 mm
housing height:	14,30 mm
housing depth:	16.75 mm
dimensional class:	slow
wire section:	1.5 mm² / 16 AWG
clamp opening size:	2.45 × 2.45 mm
wire stripping:	max 9 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	16A
voltage:	250V
test voltage:	2 kVrms/60s

MECHANICAL CHARACTERISTICS

spring releasing:	0.6 x 3.5mm
-	-

APPROVALS DATA

	-	-	-
current:	-	-	-
voltage:	-	-	-
FILE:	-	-	-

MATERIALS

housing:	PA - UL 94 V0
screw:	n/a
clamp/spring:	

AVAILABLE COLOURS

GN GY BK BL RD YL OG

other colours: upon request

Copyright ©2014 - euroclamp - http://www.euroclamp.it

terminal: Tin-plated copper alloy

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
01	MG101-5,08-P	N/A	N/A	N/A
..	MG1..-5,08-P	N/A	N/A	N/A

Copyright ©2014 - euroclamp - http://www.euroclamp.it