

Standard extruded heatsinks

<p>art. no.</p>		
<p><b>SK 185 ...</b> extruded heatsink for PCB mounting → A 104</p>		
<p>please indicate: ... <math>\left[ \right]</math> 37.5 50 1000 mm ... <math>\diamond</math> (optional) TO 3; CB</p>		
<p>art. no.</p>		
<p><b>SK 48 ...</b></p>		
<p>please indicate: ... <math>\left[ \right]</math> 37.5 50 75 100 1000 mm ... <math>\diamond</math> (optional) SSR 3; TO 3; CB</p>		
<p>art. no.</p>		
<p><b>SK 79 ...</b> with slots for cover plates or PCBs</p>		
<p>please indicate: ... <math>\left[ \right]</math> 37.5 50 75 100 1000 mm ... <math>\diamond</math> (optional) TO 3; CB</p>		
<p>art. no.</p>		
<p><b>SK 08 ...</b> with slots for cover plates or PCBs</p>		
<p>please indicate: ... <math>\left[ \right]</math> 37.5 50 75 100 1000 mm ... <math>\diamond</math> (optional) TO 3; CB</p>		
<p>art. no.</p>		
<p><b>SK 88 ...</b> with slots for cover plates or PCBs</p>		
<p>please indicate: ... <math>\left[ \right]</math> 37.5 50 75 100 1000 mm ... <math>\diamond</math> (optional) TO 3</p>		