



MATERIAL
 INSULATOR: PBT +30% GLASS FIBER (UL94V-0)
 CONTACT: PHOSPHOR BRONZE
 CONTACT PLATED: GOLD OVER NICKEL
 SPECIFICATION:
 CURRENT RATE: 1A
 INSULATOR RESISTANCE: 1000M OHM MIN OF 500V DC
 CONTACT RESISTANCE: 20mOHM MAX OF 6V DC 0.3A
 VOLTAGE: 500V AC FOR ONE MINUTE.
 OPERATING TEMPERATURE: -40°C~105°C

CIRCUITS	DIM. A	DIM. B	CIRCUITS	DIM. A	DIM. B
6	12.18	5.08	26	37.70	30.48
8	14.72	7.62	30	42.70	35.56
10	17.40	10.16	34	47.84	40.64
12	19.80	12.70	40	55.58	48.26
14	22.45	15.24	50	68.14	60.96
16	25.08	17.78	60	81.04	73.66
20	30.20	22.86	64	85.84	78.74
24	35.04	27.94			

F				DRAWN: Jerry Chen	GENERAL TOLERANCE: .X=±0.2 .XX=±0.15	DESCRIPTION: IDC SOCKET	SIZE A4
E							
D				CHECKED: Ruby	UNIT: MM	PART NO: 4401-XXSR	
C							
B				APPROVAL: Jerry Chen	SCALE:	PROJECTION:	
A	12-03-1998	4401-XXSR	Jerry Chen				
REV	DATE	FILE	BY	Mike Wu			