



Model: LP602945		Min. Capacity 最低容量 (mAh) (0.2C, 25±3°C)		700
Battery pack specification 电池组规格		*Single cell capacity (单体电芯容量) (0.2C, 25±3°C)		750
		*Single cell capacity (单体电芯容量)		
Nominal Voltage 标称电压 (V)		3.7		
Internal impedance 内阻 (≤)		200		
Charge Temp. 充电温度 (°C)		0-45		
Discharge Temp. 放电温度 (°C)		-20-60		
Humidity(湿度)		65±20%		
Ambient Conditions (环境温度)				

Overcharge Detection Voltage (V)		4.28±0.05
Overdischarge Detection Voltage (V)		3.0±0.1
Limited to Max loading current 仅用于最大的负载电流		
peak value (A)	constant (A)	constant (A)
峰值 2.0 (A)	持续 1.0 (A)	持续 1.0 (A)
Customer required Max loading current 客户要求最大的负载电流		
peak value (A)	constant (A)	constant (A)
峰值 (A)	持续 (A)	持续 (A)

Battery protection Related Value: (相关的电芯保护值)

If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如果实际应用的负载电流大于 EEMB 提供值, 请提出来, 实际的应用情况为 PCM 的设计至关重要)

Remark(备注):

- No scratch, distortion, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
- Rohs compliant(严格按照ROHS要求生产).

Title		LP602945-PCM-LD/	
File NO.		A14348	

Drawn: YanF		Revise No.:	
Checked 1: Erica		Projection:	
Checked 2:		Page: 1/1	
Approved:		Scale: 1:1	
Draw Date: 2017/07/12		Unit: mm	