

## Data sheet

246-101

## FEMALE CONNECTOR COMPLETE WITH FIXING SCREWS M4 SIDE-ENTRY CAGE CLAMP CONNECTION



## Technical data

Package size 15 pieces.

pole count	20
Cross section from [mm <sup>2</sup> ]	0.08 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	2.5 mm <sup>2</sup>
Cross section from [AWG]	28 AWG
Cross section to [AWG]	14 AWG
Voltage UL	300/600 V
Voltage CSA	300/150 V
Current UL	15/5 A
Current CSA	10/15 A
Measured voltage EN	400 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	16 A
Weight	70.55 g
Color	grey
Wiring type	Side-entry
Strip length from	8 mm
Strip length to	10 mm
Strip length	0.35 in

---

Data sheet

246-101

**FEMALE CONNECTOR COMPLETE WITH FIXING SCREWS M4  
SIDE-ENTRY CAGE CLAMP CONNECTION**

---

Approval	Voltage	Current	Approval number	Notes
CSA	300/150	10/15	18677-19	
UL	300/600	15/5	E45172	
VDE	400	16	2574-1431-1040/A1B	

---

**Data sheet**

246-101

**FEMALE CONNECTOR COMPLETE WITH FIXING SCREWS M4  
SIDE-ENTRY CAGE CLAMP CONNECTION**

---

**Accessories****Item number**

ADJACENT JUMPER UNPLATED	246-103
JUMPER POSITION MARKER	246-108
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-257
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-258
SCREWDRIVER Type 2, bar (3,5 x 0,5) mm	210-120
SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 2, bar (3,5 x 0,5) mm	210-620