

Data sheet

233-416

PCB TERMINAL STRIP 2 SOLDER PINS / POLE
PIN SPACING 2.54 MM / 0.1 IN FRONT-ENTRY CAGE CLAMP CONNECTION



Technical data

Package size 100 4*25 pieces.

Pin spacing from	2.54 mm
Pin spacing from	0.1 in
pole count	16
Cross section from [mm ²]	0.08 mm ²
Cross section to [mm ²]	0.5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	20 AWG
Voltage UL	150 V
Voltage CSA	150 V
Current UL	4 A
Current CSA	4 A
Measured voltage EN	250 V
Measured shock voltage	2.5 kV
Pollution degree	2
Current intensity EN	6 A
Weight	5.482 g
Color	orange
Wiring type	Angled Type
No. of connection Points	16
No. of potentials	16
Height	11.7 mm
Height	0.461 in
Width	42.94 mm

Data sheet**233-416****PCB TERMINAL STRIP 2 SOLDER PINS / POLE
PIN SPACING 2.54 MM / 0.1 IN FRONT-ENTRY CAGE CLAMP CONNECTION**

Width	1.691 in
Depth	12.1 mm
Depth	0.476 in
Strip length from	5 mm
Strip length to	6 mm
Strip length	0.22 in

Data sheet

233-416

**PCB TERMINAL STRIP 2 SOLDER PINS / POLE
PIN SPACING 2.54 MM / 0.1 IN FRONT-ENTRY CAGE CLAMP CONNECTION**

Approval	Voltage	Current	Approval number	Notes
BV	250	6	11915/A0	
CSA	150	4	154112-1465035	
CSM	250	4	017956	
DEMKO	130		100741	
DEMKO	250	4	DK96-03660	
DNV	250	4	E6998	
GL	250	4	17296-00HH	
KEMA	250	6	90.6212.01/02	
RMR	250	4	99.00007.250	
RosTesT	250	4	B09523	
SEMKO	250		9043004	
UL	150	4	E45172	

Data sheet

233-416

**PCB TERMINAL STRIP 2 SOLDER PINS / POLE
PIN SPACING 2.54 MM / 0.1 IN FRONT-ENTRY CAGE CLAMP CONNECTION**


Accessories**Item number**

OPERATING TOOL FOR SERIES 233 AND 733	233-332
OPERATING TOOL FOR SERIES 233 AND 733	233-335
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 2.54 MM; SERIES 233, 234	249-156
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 2.54 MM; SERIES 233, 234	249-157
SELF-ADHESIVE MARKER STRIPS SUITABLE FOR TERMINAL STRIPS WITH PIN SPACING 2.54 MM; SERIES 233, 234	249-158

Data sheet

233-416

PCB TERMINAL STRIP 2 SOLDER PINS / POLE
PIN SPACING 2.54 MM / 0.1 IN FRONT-ENTRY CAGE CLAMP CONNECTION



Data sheet

233-416

**PCB TERMINAL STRIP 2 SOLDER PINS / POLE
PIN SPACING 2.54 MM / 0.1 IN FRONT-ENTRY CAGE CLAMP CONNECTION**

Diameter of drilled hole: $1,1^{+0,1}$ mm
L = (No.of poles x pin spacing) + 2,3 mm