


Item no.: 294-8135  
 Product description: TERMINAL BLOCK FOR FIELD CONNECTION WITH DIRECT CONTACT OF THE GROUND CONDUCTOR DA+ / DA- / L / PE / N 5 POLE



Produkt kann von Bild abweichen / product may differ

Packing unit 250 pieces

RoHS compliant

Color	white
pole count	5
Height	22.4 mm
Height	0.882 in
Width	50 mm
Width	1.969 in
Depth	27.3 mm
Depth	1.075 in
Connection type	Leiteranschluss
Pollution degree	2
Measured voltage EN	500 V
Measured shock voltage	4 kV
Current intensity EN	24 A
T Identification	T 85
Pollution degree	2
Measured voltage EN	500 V
Measured shock voltage	4 kV
Current intensity EN	24 A

T Identification  
Connection type  
Degree of Protection  
Storage temperature

T 85  
Linect®-Steckverbindung  
IP 2 XC  
-35 °C to +85 °C



Processing Temperature	-5 °C to +40 °C
Connection method	CAGE CLAMP®S Connection
Cross section [mm²]	0.5 - 2.5 mm²
Cross section [AWG]	18 - 12 AWG
Wiring method	solid, stranded or fine-stranded
Number of strands	2
Cross section [mm²]	0.5 - 1.5 mm²
Cross section [AWG]	18 - 14 AWG
Wiring method	with ferrule
Number of strands	2
Connection method	PUSH WIRE®
Cross section [mm²]	0.5 - 2.5 mm²
Cross section to [AWG]	18 - 14 AWG
Wiring method	Solid
Cross section [mm²]	0.5 - 1.5 mm²
Cross section to [AWG]	18 - 14 AWG
Wiring method	with ferrule
Cross section from [mm²]	0.5 mm²
Cross section to [mm²]	1.5 mm²
Cross section from [AWG]	18 AWG
Cross section to [AWG]	16 AWG
Wiring method	Solid



Cross section from [mm <sup>2</sup> ]	0.5 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	1 mm <sup>2</sup>
Cross section from [AWG]	18 AWG
Cross section to [AWG]	16 AWG
Wiring method	with ferrule
Cross section from [mm <sup>2</sup> ]	0.5 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	0.75 mm <sup>2</sup>
Cross section from [AWG]	18 AWG
Wiring method	solid
Strip length from	8 mm
Strip length to	9 mm
Material group	IIIa

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected