

Charging socket type 2 IP54 up to 63A with RGB LED and connector lock

Charging socket type 2 IP54 up to 63A with RGB LED and connector lock, for installation in charging stations

Info

Robust and durable charging socket for frequent connection



UV-resistant



Reliability



Robust



Oil-resistant



Assembly time



Mechanical resistance



Corrosion-resistant



Good chemical resistance



e-Mobility



Suitable for outdoor use

Last Update (29.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

Charging socket type 2 IP54 up to 63A with RGB LED and connector lock

Cold-resistant

Benefits

Charging socket and controller are optimally suited

Application range

for installation in charging stations

Product features

5 different versions for all installation situations

Charging socket type 2 according to IEC62196-1.2 and IEC 61851-1

Optionally available: Hinged lid locking, RGB LED, flat design

DesignScrew connection for 3P+N+PE as well as PP and CP
with easy CONTACT and silver-plated contactsConnector lock with integrated actuator
hinged cover included**Technical Data**

Classification:	ETIM 5.0 Class-ID: EC002839 ETIM 5.0 Class-Description: Accessories for battery/charger
Nominal voltage:	200/346 V – 240/415 V
Protection rating:	IP 54
Temperature range:	-30°C to +50°C

Note

Unless otherwise specified, the product values shown are nominal values. You can receive further values, such as tolerances, upon request if they are available and have been released for publication.

Copper price basis: EUR 150/100 kg; see catalogue appendix T17 for the application and definition of "Metal price basis" and "Metal index"

Photographs are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.



Charging socket type 2 IP54 up to 63A with RGB LED and connector lock

Article number	Charging current	Article designation
Charging socket type 2 with RGB LED		
74880212	≤ 20A	EVCP2 Controller 74880215 or 74880218
74880213	≤ 32A	EVCP2 Controller 74880215 or 74880218
74880214	≤ 63A	EVCP2 Controller 74880215 or 74880218

Last Update (29.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03_16