




Stainless Bezel-free Waterproof Panel PC

		Stainless 10.4"	Stainless 15.1"	Stainless 19"	
 <p>The back panel I/O is flexible for customized configuration.</p>					
					
					
					
Model Name		10.4" + 2I385HW	15.1" + 2I385HW	19" + 2I385HW	
Dimension (mm)		308W x 45H x 259.4D mm	414W x 45H x 346.1D mm	476.4W x 45 H x 404.6D mm	
Weight		3.35 Kg	6.13 Kg	7.5 Kg	
Hard drive		2.5" HDD	2.5" HDD	2.5" HDD	
LCD brand		AUO	AUO	AUO	
LCD size		10.4 inch, 4:3	15 inch, 4:3	19 inch, 4:3	
Max Resolution		1024 x 768	1024 x 768	1280 x 1024	
Luminance (cd/m ²)		400	450	350	
Contrast Ratio		700:1	800:1	1000:1	
Viewing Angle (H-V)		60(U), 80(D), 80(R), 80(L)	80(U), 80(D), 80(R), 80(L)	60(U), 80(D), 80(R), 80(L)	
Backlight		LED	LED	LED	
Touch Screen		Resistive touch screen	Resistive touch screen	Capacitive touch screen	
MB		2I385HW	2I385HW	2I385HW	
CPU		Intel Bay Trail-H E3825 1.33 GHz (Dual Core)	Intel Bay Trail-H E3825 1.33 GHz (Dual Core)	Intel Bay Trail-H E3825 1.33 GHz (Dual Core)	
Chipset		Intel Bay Trail-H E3845 1.91 GHz (Quad Core)	Intel Bay Trail-H E3845 1.91 GHz (Quad Core)	Intel Bay Trail-H E3845 1.91 GHz (Quad Core)	
Memory	Type / Capacity	E3825 DDR3L 1066MT/s E3845 DDR3L 1333MT/s	E3825 DDR3L 1066MT/s E3845 DDR3L 1333MT/s	E3825 DDR3L 1066MT/s E3845 DDR3L 1333MT/s	
	On board memory	2 / 4GB	2 / 4GB	2 / 4GB	
SSD Storage	mSATA	Yes	Yes	Yes	
VGA		5 Selectable I/O connectors of LAN / COM / USB / VGA	5 Selectable I/O connectors of LAN / COM / USB / VGA	5 Selectable I/O connectors of LAN / COM / USB / VGA	
USB					
COM					
Mini-PCIe					
SIM Card Holder					
GPIO		4DI / 4DO (Optional)	4DI / 4DO (Optional)	4DI / 4DO (Optional)	
Ethernet		Intel GbE x 2 (5 Selectable I/O connectors of LAN / COM / USB / VGA)	Intel GbE x 2 (5 Selectable I/O connectors of LAN / COM / USB / VGA)	Intel GbE x 2 (5 Selectable I/O connectors of LAN / COM / USB / VGA)	
Audio		Line-out / Mic-in (Optional)	Line-out / Mic-in (Optional)	Line-out / Mic-in (Optional)	
Power Input		Wide Range +9~36V	Wide Range +9~36V	Wide Range +9~36V	
Battery		option (3500~10500mAh)	option (3500~10500mAh)	option (3500~10500mAh)	
Mounting		VESA 100 & Panel Mount	VESA 100 & Panel Mount	VESA 100 & Panel Mount	
Panel frame water proof		IP66 / IP67	IP66 / IP67	IP66 / IP67	
Optional MB		2I847H	2I847H	2I847H	
Expansion		GPS, 3G / 4G, Bluetooth, WI-FI, I/O, Video Card	GPS, 3G / 4G, Bluetooth, WI-FI, I/O, Video Card	GPS, 3G / 4G, Bluetooth, WI-FI, I/O, Video Card	
Operating Temp.		-20°C~60°C for mSATA / SSD HDD	-20°C~60°C for mSATA / SSD HDD	-20°C~60°C for mSATA / SSD HDD	
Operating Humidity		5~90% @ 39°C, non-condensing	5~90% @ 39°C, non-condensing	5~90% @ 39°C, non-condensing	