

Item no.: 284-101  
 Product description: 2-CONDUCTOR THROUGH TERMINAL BLOCK; LATERAL MARKING; CARRIER RAIL DIN 35; SIDE-ENTRY; CAGE CLAMP®CONNECTION; HORIZONTAL TYPE



Packing unit 50 pieces

Cross section from [mm <sup>2</sup> ]	0,2 mm <sup>2</sup>
Cross section to [mm <sup>2</sup> ]	10 mm <sup>2</sup>
Cross section from [AWG]	24 AWG
Cross section to [AWG]	08 AWG
Connection method	CAGE CLAMP®CONNECTION
Voltage CSA	600 V
Voltage UL	600 V
Current CSA	65 A
Measured voltage EN	800 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	57 A
Current UL	50 A
Weight	18,121 g
Color	grey
Wiring type	Side-entry
No. of connection Points	2
No. of potentials	1
Height	41,5 mm
Height	1,63 in
Width	10 mm
Width	0,394 in
Depth	52 mm
Depth	2,05 in
Strip length from	12 mm
Strip length to	13 mm
Strip length	0,49 in

	Admission office	Approval no.	Voltage [ V ]	Current [ A ]	Cross section [ mm <sup>2</sup> ]
284-101	BBJ	B/12/700/03	800	76	10
284-101	BV	07436/Co	800	76	10
284-101	CCA	NL3715	800	76	10
284-101	CSA	154112-1536073	600	65	24-8
284-101	CSM	017956	800	76	10
284-101	DEMKO	76761	750		10
284-101	Dep.MaE	CS4869N	600	60	10
284-101	DNV	E6999	800	57	10
284-101	GL	17295-00HH	800	57	10
284-101	KEMA	98.2759.07	800		10
284-101	KR	HMB05880-EL001	800	63	10

284-101	LR	91/20112(E1)	800	76	10
284-101	PRS	TE/1219/880590/98	800	76	10
284-101	RMR	99.00007.250	800	76	10
284-101	RosTesT	B09523	800	76	10
284-101	UL	E45172	600	50	24-8

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected