
Item no.: 264-737/999-950
Product description: 4-CONDUCTOR MINIATURE GROUND CONDUCTOR
TERMINAL BLOCK SUITABLE FOR EX E APPLICATIONS



Produkt kann von Bild abweichen / product may differ

Packing unit 100 pieces

RoHS compliant

Product group	9 (Std Chassis Mt Blocks)
Cross section [mm ²]	0.5 - 2.5 mm ²
Cross section [AWG]	20 - 12 AWG
Connection method	CAGE CLAMP® CONNECTION
Number of strands	2
Weight	8.86 g
Color	green-yellow
Wiring type	Front-entry
No. of connection Points	4
No. of potentials	1
Height	24.5 mm
Height	0.96 in
Width	10 mm
Width	0.394 in
Depth	46.5 mm
Depth	1.83 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
264-737/999-950	ABS	04-HG476174/1-PDA			2,5
264-737/999-950	AEX	E185892			28-12
264-737/999-950	CSA	18677-23			26-12
264-737/999-950	DNV	E-9215	800	24	2,5
264-737/999-950	GL	17295-00HH			2,5
264-737/999-950	GOSENERGO-Ex	99.041			2,5
264-737/999-950	PRS	TE/1718/880590/08			2,5
264-737/999-950	PTB	IECExPTB04.0003U			2,5
264-737/999-950	PTB	PTB98ATEX3129U			2,5
264-737/999-950	RosTest	8189158			2,5
264-737/999-950	UR	E45172			28-12

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected