

# UNI-T® UT200 SERIES

## 1000A Digital Clamp Meters

UT205A ■ UT206A



■ UT205A



■ UT206A

### SPECIFICATIONS



Specifications	Range	Best Accuracy	
		UT205A	UT206A
Model		<b>UT205A</b>	<b>UT206A</b>
AC Current (A)	400A/1000A	±(1.5%+5)	±(1.5%+5)
AC Voltage (V)	4V/40V/400V/600V	±(1.2%+5)	±(1.2%+5)
DC Voltage (V)	400mV/4V/40V/400V/600V	±(0.8%+1)	±(0.8%+1)
Resistance (Ω)	400Ω/4KΩ/40KΩ/400KΩ/4MΩ/40MΩ	±(1%+2)	±(1%+2)
Frequency (Hz)	10Hz~10MHz	±(0.1%+3)	±(0.1%+3)
Temperature (°C)	-40 °C ~ 1000°C		±(2%+8)
<b>Features</b>			
Display Count		3999	3999
Auto Range		✓	✓
Jaw Capacity		40mm	40mm
Duty Cycle	0.1%~99.9%	✓	
Diode		✓	✓
Auto Power Off		✓	✓
Continuity Buzzer		✓	✓
Low Battery Indication		✓	✓
Data Hold		✓	✓
Relative Mode			✓
LCD Backlight		✓	✓
Full Icon Display		✓	✓
Input Impedance for DCV	Around 10MΩ	✓	✓

### GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	37mm × 18 mm
Product Color	Red and Grey
Product Net Weight	350g
Product Size	236mm × 97mm × 40mm
Standard Accessories	UT205A-Battery, Test Lead, Carrying Bag
	UT206A-Battery, Test Lead, Carrying Bag, Point Contact Temperature Probe
Standard Individual Packing	Gift Box, English Manual
Standard Quantity Per Carton	20 PCs
Standard Carton Measurement	530mm × 360mm × 385mm (0.073 CBM Per Standard Carton)
Standard Carton Gross Weight	17Kg