

STICK18X,25,31X,34X,36X

# R F I D   S T I C K   T A G

STICK TAG OF VARIOUS SIZE AND MATERIAL



STICK18R



STICK18BU




STICK18GE



STICK18Y



STICK18BK



STICK25



STICK31GY



STICK34GY



STICK36GY



STICK34W



STICK34GE



STICK34BU



STICK34R

## RFID Stick Specification

Model No.	STICK18	STICK25	STICK31	STICK34	STICK36
Thickness	2.43mm	0.6mm	60mm	60mm	60mm
Reading Distance	60mm	70mm			
Base on GK4001 chip, with EM9917 reader					
Size	∅18mm	∅25mm	31mm	51mm x 25mm	30mm x 40mm
Operating temperature	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C	-40°C to 70°C
Storage temperature	-40°C to 80°C	-40°C to 80°C	-40°C to 80°C	-40°C to 80°C	-40°C to 80°C
Water proof	Yes	Yes	Yes	Yes	Yes
Material	Poly	PVC	PVC+EPVC	PVC+EPVC	PVC+EPVC
<b>Technology</b>					
GK4001 (125KHz, 64bit, R/O)	Y	Y	Y	Y	Y
H4102 (125KHz, 64bit, R/O)	Y	Y	Y	Y	Y
I-Code SLI (13.56MHz, 1024bit, R/W)	N	Y	Y	Y	Y
Mifare S50 (13.56MHz, 1KByte, R/W)	N	Y	Y	Y	Y
Temic E5557 (125KHz, 330bit, R/W)	Y	Y	Y	Y	Y
Hitag 1 (125KHz, 2048bit, R/W)	Y	Y	Y	Y	Y
Hitag 2 (125KHz, 256bit, R/W)	Y	Y	Y	Y	Y
Legic 256 (13.56MHz, 256Byte, R/W)	N	Y	Y	Y	Y

**Application:** Car stick to various kind of goods for it's application management purposes.