

Item no.: 260-331
 Product description: 4-CONDUCTOR TERMINAL BLOCK;
 LATERAL MARKING; WITH MOUNTING
 FEET 209-123 FOR TS 35; SIDE-ENTRY;
 CAGE CLAMP®CONNECTION;
 HORIZONTAL TYPE



Packing unit 300 6*50 pieces

| | |
|---------------------------------------|-----------------------|
| Cross section from [mm ²] | 0,08 mm ² |
| Cross section to [mm ²] | 1,5 mm ² |
| Cross section from [AWG] | 28 AWG |
| Cross section to [AWG] | 16 AWG |
| Connection method | CAGE CLAMP®CONNECTION |
| Number of strands | 2 |
| Voltage CSA | 300 V |
| Voltage UL | 300 V |
| Current UL | 10 A |
| Current CSA | 15 A |
| Measured voltage EN | 400 V |
| Measured shock voltage | 6 kV |
| Pollution degree | 3 |
| Current intensity EN | 18 A |
| Weight | 2,55 g |
| Color | grey |
| Wiring type | Side-entry |
| No. of connection Points | 4 |
| No. of potentials | 1 |
| Height | 17 mm |
| Height | 0,669 in |
| Width | 8 mm |
| Width | 0,315 in |
| Depth | 25 mm |
| Depth | 0,985 in |
| Strip length from | 8 mm |
| Strip length to | 9 mm |
| Strip length | 0,33 in |

| | Admission office | Approval no. | Voltage [V] | Current [A] | Cross section [mm ²] |
|---------|------------------|--------------|------------------|------------------|--------------------------------------|
| 260-331 | BBJ | B/12/696/03 | 400 | 17,5 | 1,5 |
| 260-331 | BV | 07436/C0 | 400 | 17,5 | 0,08-1,5 |
| 260-331 | CCA | DK96-00357 | 400 | 17,5 | 1,5 |
| 260-331 | CSA | 18677-45 | 300 | 15 | 24-16 |
| 260-331 | DEMKO | 120039 | 400 | 17,5 | 1,5 |
| 260-331 | Dep.MaE | CS4590N | 300 | 20 | |

| | | | | | |
|---------|---------|-------------------|-----|------|-------|
| 260-331 | DNV | E6998 | 400 | 17,5 | 1,5 |
| 260-331 | GL | 17295-00HH | 400 | 17,5 | 1,5 |
| 260-331 | KEMA | 92.6446.01 | 500 | | 1,5 |
| 260-331 | KR | HMB05880-EL002 | 400 | 17,5 | 1,5 |
| 260-331 | LR | 91/20242(E3) | 500 | 19,5 | 1,5 |
| 260-331 | NEMKO | M59289/02 | 500 | | 1,5 |
| 260-331 | PRS | TE/1219/880590/98 | 400 | 17,5 | 1,5 |
| 260-331 | RMR | 99.00007.250 | 400 | 17,5 | 1,5 |
| 260-331 | RosTesT | B09523 | 400 | 17,5 | 1,5 |
| 260-331 | SEMKO | 9408057 | 500 | | 1,5 |
| 260-331 | UL | E45172 | 300 | 10 | 28-16 |
| 260-331 | VDE | 207 ÜG,Bl.1 | 500 | | 1,5 |

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected