



HHR-80AAAB Cylindrical AAA size (HR11/45)

B type

Dimensions (with tube) (mm)



Typical charge characteristics



Specifications

Diameter	10.5+0 / -0.7mm
Height	44.5+0 / -1.0mm
Approximate Weight	13g

Nominal Voltage		1.2V
Discharge Capacity	Average ^{*1}	780mAh
	Rated (min.)	750mAh
Approx. Internal impedance at 1000Hz at charged state.		35m Ω
Charge	Standard	75mA X 16hrs.
	Rapid ^{*3}	750mA X 1.7hrs.
Ambient Temperature	Charge	Standard: 0°C to 45°C Rapid: 0°C to 40°C
	Discharge	-10°C to 65°C
Storage	<1 year	-20°C to 35°C
	<6 months	-20°C to 45°C
	<1 month	-20°C to 55°C



*1 After charging at 0.1It for 16 hours, discharging at 0.2It.

*2 For reference only.

*3 Need specially designed control system. Please contact Panasonic for details.

Battery performance and cycle life are strongly affected by how they are used. In order to maximize battery safety, please consult Panasonic when determining charge/discharge specs, warning label contents and unit design.

Typical discharge characteristics



*The data in this document are for descriptive purposes only and are not intended to make or imply any guarantee or warranty.