


## PTSM 0,5/ 3-HH-2,5-SMD R32

Order No.: 1778777

<http://eshop.phoenixcontact.co.uk/phoenix/treeViewClick.do?UID=1778777>

Header, Nominal current: 6 A, Rated voltage (III/2): 160 V, Number of positions: 3, Pitch: 2.5 mm, Color: Black, Contact surface: Tin, Assembly: SMD/THT/THR

Commercial data	
EAN	 4 046356 529983
Pack	600
Customs tariff	85369010
Country of Origin	DE
Catalog page information	Page 57 (CC-2011)

### Product notes

WEEE/RoHS-compliant since:  
17/09/2009



Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation at <http://www.download.phoenixcontact.com>. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
<b>Dimensions / positions</b>	
Length	7.5 mm
Pitch	2.5 mm
Dimension a	5 mm
Number of positions	3
Pin spacing	2.50 mm

### Technical data


Range of articles	PTSM 0,5/...-HH-SMD
Insulating material group	IIIa
Rated surge voltage (III/3)	2.5 kV
Rated surge voltage (III/2)	2.5 kV
Rated surge voltage (II/2)	2.5 kV
Rated voltage (III/2)	160 V
Rated voltage (II/2)	160 V
Connection in acc. with standard	EN-VDE
Nominal current $I_N$	6 A
Nominal voltage $U_N$	50 V
Maximum load current	6 A
Insulating material	LCP
Inflammability class according to UL 94	V0
Color	Black
Nominal voltage, UL/CUL Use Group B	150 V
Nominal current, UL/CUL Use Group B	6 A

### Certificates


Certification CUL, GOST, UL

### Drawings

Drilling plan/solder pad geometry



Dimensioned drawing



Connection data incl. use groups





**Address**

PHOENIX CONTACT Ltd  
Halesfield 13  
Telford / Shropshire / TF7 4PG,England  
Phone 01952 681 700  
Fax 01952 681 799  
<http://www.phoenixcontact.co.uk>



Phoenix Contact Ltd.  
Technical modifications reserved;