



**Part Number: 9842**

RS-485, (2 pr) 24 AWG (7x32) TC, PE/PVC, Foil+TC Braid Shld, CM, 120Ω

## Product Description

Two 24 AWG pairs stranded (7x32) tinned copper conductors, polyethylene insulation, twisted pairs, overall Beldfoil® (100% coverage) + tinned copper braid shield (90% coverage), 24 AWG stranded tinned copper drain wire, PVC jacket.

## Technical Specifications

### Product Overview

Suitable Applications:	RS-485, DMX-512
------------------------	-----------------

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Conductors	No. of Pairs
24	7x32	TC - Tinned Copper	4	2

Conductor Count:	4
Total Number of Pairs:	2
Conductor Size:	24 AWG

#### Insulation

Material	Nominal Wall Thickness
PE - Polyethylene	0.022 in

#### Color Chart

Number	Color
1	White/Blue & Blue/White
2	White/Orange & Orange/White

#### Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	1	Aluminum/Polyester	Beldfoil®	100 %	TC - Tinned Copper	24	7x32 mm
Braid	2	TC - Tinned Copper		90 %			

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.34 in	0.035 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
24 Ohm/1000ft	2.2 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
12.8 pF/ft	23 pF/ft

#### Impedance

#### Nominal Characteristic Impedance

120 Ohm

#### High Frequency (Nominal/Typical)

##### Frequency [MHz] | Nom. Insertion Loss

1 MHz | 0.6 dB/100m

#### Delay

##### Max. Delay Skew | Nominal Delay | Nominal Velocity of Propagation (VP) [%]

66 ns/100m | 1.54 ns/ft | 66 %

#### Current

##### Max. Recommended Current [A]

Per conductor @ 25°C: 2.1 A

#### Voltage

##### UL Voltage Rating

300 V RMS

#### Temperature Range

UL Temp Rating:	80°C
Operating Temp Range:	-30°C To +80°C

#### Mechanical Characteristics

Bulk Cable Weight:	49 lbs/1000ft
Max Recommended Pulling Tension:	87 lbs
Min Bend Radius/Minor Axis:	3.5 in

#### Standards

NEC Articles:	800
NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
UL AWM Style:	2919 (30 V 80°C)
CPR Euroclass:	Eca

#### Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

#### Suitability

Suitability - Indoor:	Yes
-----------------------	-----

#### Flammability, LS0H, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

#### Plenum/Non-Plenum

Plenum (Y/N):	N
Plenum Number:	82842

#### Part Number

#### Variants

Item #	Color	UPC	Length	Footnote
9842.001000	Chrome		1,000 m	
9842.00152	Chrome		152 m	
9842.001525	Chrome		1,525 m	
9842.0030	Chrome		30 m	
9842.00305	Chrome		305 m	
9842.00500	Chrome		500 m	
9842.009999	Chrome		151 m	
9842 060100	Chrome	612825259510	100 ft	
9842 0601000	Chrome	612825259527	1,000 ft	C
9842 06010000	Chrome	612825259534	10,000 ft	
9842 060500	Chrome	612825259541	500 ft	C
9842 0605000	Chrome	612825259558	5,000 ft	
9842.K0305	Chrome		305 m	
9842.K01525	Chrome		1,525 m	

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.