

Data sheet

280-560

SENSOR TERMINAL BLOCK CENTRE MARKING ANGLED TYPE-ENTRY CAGE CLAMP CONNECTION ANGLED TYPE



Technical data

Package size 50 pieces.

Cross section from [mm ²]	0.08 mm ²
Cross section to [mm ²]	2.5 mm ²
Cross section from [AWG]	28 AWG
Cross section to [AWG]	12 AWG
Voltage UL	300 V
Voltage CSA	300 V
Current UL	15 A
Current CSA	15 A
Measured voltage EN	400 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	20 A
Weight	10.57 g
Color	grey
Wiring type	Angled Type
No. of connection Points	4
No. of potentials	3
Height	55.5 mm
Height	2.19 in
Width	5 mm
Width	0.197 in
Depth	80 mm
Depth	3.15 in

Data sheet

280-560

**SENSOR TERMINAL BLOCK CENTRE MARKING
ANGLED TYPE-ENTRY CAGE CLAMP CONNECTION ANGLED TYPE**

Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in

Data sheet

280-560

**SENSOR TERMINAL BLOCK CENTRE MARKING
ANGLED TYPE-ENTRY CAGE CLAMP CONNECTION ANGLED TYPE**

Approval	Voltage	Current	Approval number	Notes
BV	500	20	07436/C0	
CSA	300	15	154112-1536071	
Dep.MaE	600	25	CS4865N	
NEMKO	500	20	L86905	
UL	300	15	E45172	

Data sheet

280-560

SENSOR TERMINAL BLOCK CENTRE MARKING ANGLED TYPE-ENTRY CAGE CLAMP CONNECTION ANGLED TYPE

Accessories	Item number
ADJACENT JUMPER NOMINAL CURRENT 24 A	280-402
ALUMINIUM CARRIER RAIL 35 X 7.5 MM, 1.5 MM / 0.059 IN THICK	210-196
COPPER CARRIER RAIL 35 X 15 MM, 2.3 MM / 0.091 IN THICK	210-198
COVER CARRIER TYPE 2	709-168
COVER TYPE 2	709-154
END AND INTERMEDIATE PLATE 1 MM / 0.039 IN THICK	280-319
END AND INTERMEDIATE PLATE 1 MM / 0.039 IN THICK	280-321
GROUP MARKER CARRIER FOR UP TO 1 WMB-MARKER OR 2 MARKER TAGS	209-142
GROUP MARKER CARRIER FOR UP TO 2 WMB-MARKER OR 5 MARKER TAGS	209-141
GROUP MARKER CARRIER FOR UP TO 3 WMB-MARKER OR 8 MARKER TAGS	209-140
Individual wire jumpers	individual jumper
INSULATION STOP 0.08 - 0.2 MM ²	280-470
INSULATION STOP 0.25 - 0.5 MM ²	280-471
INSULATION STOP 0.75 - 1 MM ²	280-472
Open individual wire jumpers ends	individual jumper open end
OPERATING STICKER FOR CAGE CLAMP, UNIVERSAL	210-416
PIVOTABLE GROUP MARKER CARRIER	249-105
PUSH-IN TYPE WIRE JUMPERS L = 180 MM/7.087 IN	249-123
PUSH-IN TYPE WIRE JUMPERS WIRE LENGTH 110 MM / 4.331 IN	249-126
PUSH-IN TYPE WIRE JUMPERS WIRE LENGTH 250 MM / 9.843 IN	249-127
PUSH-IN TYPE WIRE JUMPERS WIRE LENGTH 60 MM / 2.362 IN	249-125
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-257
SCREWDRIVER 3.5 X 0.5 MM / 0.137 X 0.019IN	210-258
SCREWDRIVER Type 2, bar (3,5 x 0,5) mm	210-120
SCREWDRIVER WITH PARTIALLY INSULATED SHAFT Type 2, bar (3,5 x 0,5) mm	210-620
SCREWLESS END STOP 10 MM / 0.394 IN WIDE	249-117
SCREWLESS END STOP 6 MM / 0.236 IN WIDE	249-116
SPARE FIXING / RETAINING SCREWS	209-196
SPARE KNURLED NUT	210-549
STAGGERED JUMPER FROM 1 TO 2	780-452
STAGGERED JUMPER FROM 1 TO 3	780-453
STAGGERED JUMPER FROM 1 TO 4	780-454
STAGGERED JUMPER FROM 1 TO 5	780-455
STAGGERED JUMPER FROM 1 TO 6	780-456
STAGGERED JUMPER FROM 1 TO 7	780-457
STAGGERED JUMPER FROM 1 TO 8	780-458
STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK	210-114
STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK	210-197

Data sheet

280-560

SENSOR TERMINAL BLOCK CENTRE MARKING ANGLED TYPE-ENTRY CAGE CLAMP CONNECTION ANGLED TYPE

STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK	210-506
STEEL CARRIER RAIL 35 X 15 MM, 1.5 MM / 0.059 IN THICK	210-508
STEEL CARRIER RAIL 35 X 15 MM, 2.3 MM / 0.091 IN THICK	210-118
STEEL CARRIER RAIL 35 X 15 MM, 2.3 MM / 0.091 IN THICK	210-548
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-112
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-113
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-162
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-229
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-504
STEEL CARRIER RAIL 35 X 7.5 MM, 1 MM / 0.039 IN THICK	210-505
WIRE COMMONING CHAIN INSULATED	210-103
WIRE COMMONING CHAIN INSULATED	210-123
WIRE COMMONING CHAIN INSULATED	709-110
WIRE COMMONING CHAIN INSULATED	709-111
WIRE COMMONING CHAIN INSULATED	709-112
WMB MULTI MARKING SYSTEM PLAIN	793-501
WMB MULTI MARKING SYSTEM PLAIN	793-5501
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-006
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-005
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-002
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-007
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-012
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-017
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-023
WMB MULTI MARKING SYSTEM PLAIN	793-501/000-024
WSB QUICK MARKING SYSTEM PLAIN	209-501
WSB QUICK MARKING SYSTEM PLAIN	209-501/000-002
WSB QUICK MARKING SYSTEM PLAIN	209-501/000-005
WSB QUICK MARKING SYSTEM PLAIN	209-501/000-006
WSB QUICK MARKING SYSTEM PLAIN	209-501/000-007
WSB QUICK MARKING SYSTEM PLAIN	209-501/000-012
WSB QUICK MARKING SYSTEM PLAIN	209-501/000-017
WSB QUICK MARKING SYSTEM PLAIN	209-501/000-023
WSB QUICK MARKING SYSTEM PLAIN	209-501/000-024

Data sheet

280-560

**SENSOR TERMINAL BLOCK CENTRE MARKING
ANGLED TYPE-ENTRY CAGE CLAMP CONNECTION ANGLED TYPE**

