

Male headers

Contact cross section □ 0.3 mm, straight, slim insulating body

- suitable for female header **BLM**
- one row 1-20 contacts

art. no.	dim. [mm]			art. no.	dim. [mm]		
	A	B	C		A	B	C
SLM N 1 063 ...	11.1	3.1	6.3	SLM N 11 063 ...	12.8	4.8	6.3
SLM N 1 092 ...	14.0	3.1	9.2	SLM N 11 117 ...	18.2	4.8	11.7
SLM N 1 117 ...	16.5	3.1	11.7				

please indicate: ... no. of contacts one row 1 - 20 ... surface of contact
G = gold-plated
Z = tin-plated

Contact cross section □ 0.4 mm, straight, slim insulating body

- matching for female header **BLM**
- one row 1-20 contacts

art. no.	dim. [mm]			art. no.	dim. [mm]		
	A	B	C		A	B	C
SLV N 1 055 ...	9.7	2.5	5.5	SLV N 11 055 ...	12.2	5.0	5.5
SLV N 1 080 ...	12.2	2.5	8.0	SLV N 11 080 ...	14.7	5.0	8.0
SLV N 1 105 ...	14.7	2.5	10.5	SLV N 11 105 ...	17.2	5.0	10.5
SLV N 1 130 ...	17.2	2.5	13.0				

please indicate: ... no. of contacts one row 1 - 20 ... surface of contact
G = gold-plated
Z = tin-plated