



## Fuse Holder - Stackable version - Pitch 11mm - 2÷6 poles

### GENERAL INFORMATION

|                        |                |
|------------------------|----------------|
| pitch:                 | 11 mm          |
| housing height:        | 34,00 mm       |
| housing depth:         | 15.32 mm       |
| dimensional class:     | n/a            |
| wire section:          | -              |
| clamp opening size:    | ∅- mm          |
| wire stripping:        | -              |
| operating temperature: | -40°C ÷ +130°C |

### ELECTRICAL CHARACTERISTICS

|               |             |
|---------------|-------------|
| current:      | 1÷40A       |
| voltage:      | -V          |
| test voltage: | 2 kVrms/60s |

### MECHANICAL CHARACTERISTICS

### APPROVALS DATA



|          |   |
|----------|---|
| current: | - |
| voltage: | - |
| FILE:    | - |

### AVAILABLE COLOURS



other colours: upon request

### MATERIALS

|               |                         |
|---------------|-------------------------|
| housing:      | PA - UL 94 V0           |
| screw:        | n/a                     |
| clamp/spring: | n/a                     |
| terminal:     | Tin-plated copper alloy |

| poles | P/N        | pcs/pack | W [Kg]* | W [Kg]* |
|-------|------------|----------|---------|---------|
| 2     | MPFA2-11-L | N/A      | N/A     | N/A     |

|   |            |     |     |     |
|---|------------|-----|-----|-----|
| 3 | MPFA3-11-L | N/A | N/A | N/A |
| 4 | MPFA4-11-L | N/A | N/A | N/A |
| 5 | MPFA5-11-L | N/A | N/A | N/A |
| 6 | MPFA6-11-L | N/A | N/A | N/A |