

Patch cable - SPE-T1-CCP-SF/2,0/AWG22/CCP-SF



1183808

<https://www.phoenixcontact.com/pc/products/1183808>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Patch cable, type: IEC 63171-2, degree of protection: IP20, cable length: 2 m, number of positions: 2, 1 Gbps, material: TPU, connection method: Crimp connection, connection cross section: AWG 22- 22, Single Pair Ethernet

Your advantages

- Compact design
- Connectors in accordance with IEC 63171-2
- Mechanical interlock with locking clip
- Robust industrial design
- 360° shielding
- Data transmission up to 600 MHz

Commercial Data

Item number	1183808
Packing unit	1 pc
Minimum order quantity	1 pc
Product Key	ABNICA
GTIN	4063151222352
Weight per Piece (including packing)	90.1 g
Weight per Piece (excluding packing)	90.1 g
Customs tariff number	85444290
Country of origin	DE

1183808

<https://www.phoenixcontact.com/pc/products/1183808>

Technical Data

Product properties

Product type	Data cable preassembled
Number of positions	2
No. of cable outlets	1
Number of slots	2
Locking type	Locking clip
Shielded	yes

Insulation characteristics

Overvoltage category	I
Degree of pollution	2

Electrical properties

Rated voltage (III/2)	72 V DC
Rated current	4 A
Frequency range	600 MHz
Insulation resistance	> 1 TΩ
Contact resistance	< 20 MΩ

Mechanical properties

Mechanical data

Insertion force per signal contact	< 10.00 N
Extraction force per signal contact	< 10 N

Material specifications

Flammability rating according to UL 94	V0
Contact material	Cu alloy
Contact surface material	Ni/Au
Contact carrier material	LCP
Housing material	TPU

Dimensions

Width	7.53 mm
Height	14 mm
Length	36 mm

Connection data

Connection technology

Connection method	Crimp connection
-------------------	------------------

Conductor connection

Connection method	Crimp connection
-------------------	------------------

Patch cable - SPE-T1-CCP-SF/2,0/AWG22/CCP-SF



1183808

<https://www.phoenixcontact.com/pc/products/1183808>

Connector

Insertion/withdrawal cycles	≥ 1000
-----------------------------	--------

Connection 1

Shielded	yes
Insertion/withdrawal cycles	≥ 750
Degree of protection	IP20

Connection 2

Shielded	yes
----------	-----

Cable / line

Cable length	2.00 m
--------------	--------

Ambient conditions

Degree of protection	IP20
Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Ambient temperature (assembly)	-40 °C ... 85 °C
Resistance to oil	yes

Standards and regulations

Flame resistance	UL 94 V0
Resistance to oil	yes
Other resistance	UV resistant


Patch cable - SPE-T1-CCP-SF/2,0/AWG22/CCP-SF



1183808

<https://www.phoenixcontact.com/pc/products/1183808>

Approvals

 UL Recognized Approval ID: File E335024				
	Nominal Voltage U_N	Nominal Current I_N	Cross Section AWG	Cross Section mm^2
		1.4 A	-	-

Patch cable - SPE-T1-CCP-SF/2,0/AWG22/CCP-SF



1183808

<https://www.phoenixcontact.com/pc/products/1183808>

Classifications

ECLASS

ECLASS-9.0	27440390
ECLASS-10.0.1	27440390
ECLASS-11.0	27440392

ETIM

ETIM 8.0	EC002943
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Patch cable - SPE-T1-CCP-SF/2,0/AWG22/CCP-SF



1183808

<https://www.phoenixcontact.com/pc/products/1183808>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Patch cable - SPE-T1-CCP-SF/2,0/AWG22/CCP-SF



1183808

<https://www.phoenixcontact.com/pc/products/1183808>

Accessories

SPE PCB connector

SPE PCB connector - SPE-T1-STRM-90 - 1163797

<https://www.phoenixcontact.com/pc/products/1163797>



SPE PCB connector, type: IEC 63171-2, degree of protection: IP20, number of positions: 2, 1 Gbps, CAT B (ISO/IEC 63171), connection method: THR solder connection, Single Pair Ethernet

SPE PCB connector

SPE PCB connector - SPE-T1-STSM-180 - 1163798

<https://www.phoenixcontact.com/pc/products/1163798>



SPE PCB connector, type: IEC 63171-2, degree of protection: IP20, number of positions: 2, 1 Gbps, CAT B (ISO/IEC 63171), connection method: THR solder connection, Single Pair Ethernet

Patch cable - SPE-T1-CCP-SF/2,0/AWG22/CCP-SF



1183808

<https://www.phoenixcontact.com/pc/products/1183808>

SPE PCB connector

SPE PCB connector - SPE-T1-STRM-90-LED - 1215778

<https://www.phoenixcontact.com/pc/products/1215778>



SPE PCB connector, type: IEC 63171-2, degree of protection: IP20, number of positions: 2, 1 Gbps, CAT B (ISO/IEC 63171), connection method: THR solder connection, Single Pair Ethernet

Phoenix Contact 2022 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com