

5-56 PRO

Technical Data Sheet

Product name: 5-56 Pro
Sales code: 32734

Creation date: 8/2016

Version: I

1: General description

A true multi-purpose toolkit in a can for professional automotive engineers. Displaces moisture, starts wet engines, prevents electrical failures. Lubricates, loosens seized and rusted mechanisms. Protects against humidity and prevents flash rust.

2: Features

- General Corrosion protection.
- Temporary conservation of metal parts during storage.
- Protects metals and alloys.
- Displaces and seals out water and moisture.
- Loosens metal parts seized by dirt, corrosion or dried-up grease.
- Penetrates quickly.
- Safe on all metal surfaces, does not stain.
- Safe on most rubbers, plastics and coatings. Test on sensitive or stressed materials before use.
- Convenient 360° (including inverted position) spray valve for aerosols.
- High purity CO2 propellant, giving an active product content of 95%.

3: Applications

- Seized and corroded parts.
- To remove moisture from ignition systems.
- Professional multipurpose automotive product.

4: Directions

- Apply a thin even film.
- Use extension tube for more precise application.
- Allow a few minutes for good penetration.
- Repeat if necessary.
- To remove residues or excess product, use CRC Power Clean Pro.
- Do not use on energized equipment.
- A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.



5: Typical product data (without propellant)

- Appearance : Liquid.
- Colour : Amber
- Odour : Salicylate.
- Density : 0.82 g/cm³ (@ 20°C).
- Flash Point : > 70 °C (Closed Cup)
- Auto Ignition temperature : > 200 °C
- Density active product : 0.88 g/cm³ (@ 20°C).
- Dynamic viscosity active product : 26 mPa.s (@ 40°C).
- Typical coat weight : 1 --> 2 µm

6: Packaging

Aerosol

12x500 ML

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.